





**7** Fr. **2** Lumen

30 cm catheter length 1032 inch dia. spring-wire guide

## **Two-Lumen CVC**

## Contents:

- Two-Lumen Catheter: 7 Fr. (2.5 mm OD) x 30 cm Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 26-3/4" (68 cm) (Straight Soft Tip
- Spring-Wire Guide, Marked: .032' (0.81 mm) dia. x 26-3/4' (68 cm) (Straight Soft Tip on One Fin on Other) with Arrow Advancer Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer Needle Injection Needle: 22 Ga. x 1-1/2" (3.81 cm) Injection Needle: 25 Ga. x 1-1/2" (3.81 cm) Injection Needle: 18 Ga. x 1-1/2" (3.81 cm) Introducer Needle: Echogenic 18 Ga. x 2-1/2" (6.35 cm) XTW Pressure Transduction Probe

- Pressure Transduction Probe Introducer Needle: 22 Ga. x 2-3/4" (7 cm) TW Syringe: 10 mL Luer-Slip

- Syringe: 3 mL Luer-Lock
  Syringe: 5 mL Luer-Lock
  Syringe: 5 mL Luer-Slip
  Arrow® Raulerson Spring-Wire Introduction Syringe: 5 mL

- SharpsAway® II Locking Disposal Cup
- Tissue Dilator: 8 Fr. (2.7 mm) x 9 cm

  Dust Cap: Non-Vented
  SecondSite™ Adjustable Hub: Fastener
  SecondSite™ Adjustable Hub: Catheter Clamp

  Medicine Cup: 60 mL

  Medicine Cup: 100 mL

  SecondSite™ Adjustable Hub: Catheter Clamp
- Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death.

Not made with natural rubber latex. Sterilized using ethylene oxide unless otherwise indicated in the contents list.

Fluid path components are non-pyrogenic.

1.	SharpsAway®	Dienneal	$C_{11}$
	Oliai parway -	Disposai	Ou

- Drape: 48" x 88" (122 cm x 224 cm) with 3-1/2" (9 cm) fenestration
- Needle Holder Scissors Scalpel: #11
- Stopcock: 4-way Label Sheet

- Cause Sheet
  Prep Sponge Swab
  Gauze Pad: 4" x 4" (10 cm x 10 cm)
  Dressing: OpSite®1 4-3/4" x 4" (12 cm x 10 cm)
  Suture: 3-0 Silk with Curved Needle 6: Gauze Pad: 4
  1: Dressing: Op
  1: Suture: 3-0 \$
  1: Tray: Prep
- <sup>1</sup>A registered trademark of T.J. Smith & Nephew, Limited.

6 Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	
Distal (16 Ga.)	0.57	1917	_
Proximal (16 Ga.)	0.62	2000	

<sup>\*</sup> Priming volumes are approximate and are done without accessories. † Flow rate values are approximate and are determined using deionized water at 100 cm head height.









Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA



LBL054865 R00 (2021-05)













