



REF SA-18763-J

7 Fr.

3 Lumen

60 cm catheter length

.035 inch dia. spring-wire guide

# Three-Lumen CVC

## Contents:

- 1: Three-Lumen Catheter: 7 Fr. (2.5 mm OD) x 60 cm

1: Spring-Wire Guide: .035" (0.89 mm) dia. x 39-1/2" (100 cm) PTFE-Coated (Straight Soft Tip on One End - "J" Tip on Other) with Arrow Advancer

1: Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer Needle

1: Injection Needle: 22 Ga. x 1-1/2" (3.81 cm)

1: Injection Needle: 25 Ga. x 1-1/2" (3.81 cm)

1: Injection Needle: 18 Ga. x 1-1/2" (3.81 cm)

1: Introducer Needle: Echogenic 18 Ga. x 2-1/2" (6.35 cm) XTW

1: Pressure Transduction Probe

1: Introducer Needle: 22 Ga. x 2-3/4" (7 cm) TW

1: Syringe: 10 mL Luer-Slip

1: Syringe: 3 mL Luer-Lock

1: Syringe: 5 mL Luer-Slip

1: Arrow® Raulerson Spring-Wire Introduction Syringe: 5 mL

1: Dilator: Intro 8 Fr. (2.7 mm) X 9.1 cm

3: Dust Cap: Non-Vented

1: SecondSite™ Adjustable Hub: Fastener

1: SecondSite™ Adjustable Hub: Catheter Clamp

2: Medicine Cup: 60 mL

1: Medicine Cup: 100 mL

1: SharpsAway® II Locking Disposal Cup
- 1: SharpsAway® Disposal Cup

1: Drape: 48" x 88" (122 cm x 224 cm) with 3-1/2" (9 cm) fenestration

1: Needle Holder

1: Scissors

1: Scalpel: #11

3: Stopcock: 4-way

1: Label Sheet

2: Prep Sponge Swab

6: Gauze Pad: 4" x 4" (10 cm x 10 cm)

1: Dressing: OpSite®<sup>1</sup> 4-3/4" x 4" (12 cm x 10 cm)

1: Suture: 3-0 Silk with Curved Needle

1: Tray: Prep

<sup>1</sup>A registered trademark of T.J. Smith & Nephew, Limited.

**Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death.**  
**Not made with natural rubber latex.**  
Sterilized using ethylene oxide unless otherwise indicated in the contents list.  
Fluid path components are non-pyrogenic.



Lumen

Priming Volume\* (mL)

Gravity Flow Rate† (mL/hr)

|                   |      |      |
|-------------------|------|------|
| Distal (16 Ga.)   | 0.80 | 1287 |
| Medial (18 Ga.)   | 0.60 | 409  |
| Proximal (18 Ga.) | 0.62 | 416  |

\* Priming volumes are approximate and are done without accessories.  
† Flow rate values are approximate and are determined using deionized water at 100 cm head height.



LOT



Arrow International LLC  
Subsidiary of Teleflex Incorporated  
3015 Carrington Mill Blvd.  
Morrisville, NC 27560 USA

Teleflex®  
www.teleflex.com

LBL054870 R00 (2021-12)



REF SA-18763-J

7 Fr.

3 Lumen

60 cm catheter length

.035 inch dia. spring-wire guide

# Three-Lumen CVC