**ARRC** 





(IPNXXXXXX)

13 cm catheter length

\_018 inch dia. spring-wire guide

## Pediatric Arrowg+ard Blue® Three-Lumen CVC

- Arrowg+ard Blue® Three-Lumen Catheter: 5.5 Fr. (1.9 mm OD) x 13 cm
- Spring-Wire Guide, Marked: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End "J" Tip on Other) with Arrow
- Advancer Catheter: 22 Ga. x 1-3/4" (4.45 cm) Radiopaque over 25 Ga. RW Introducer Needle
- Introducer Needle: 21 Ga. x 1-1/2" (3.81 cm) TW Syringe: 5 mL Luer-Slip

- Tissue Dilator: 6 Fr. (2.0 mm) x 7.6 cm Tissue Dilator: 6 Fr. (2.0 mm) x 4.1 cm

- Dust Cap: Non-Vented
  SecondSite™ Adjustable Hub: Fastener
  SecondSite™ Adjustable Hub: Catheter Clamp

All components are CE 2797 unless otherwise noted.

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU

California Prop. 65

▲ WARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov

Not made with natural rubber latex.

Store below 25°C (77°F). Avoid excessive heat above 40°C (104°F). Fluid path components are non-pyrogenic.

Contraindications: The Arrowg+ard Blue antimicrobial catheter is contraindicated for patients with known hypersensitivity to chlorhexidine, silver sulfadiazine and/or sulfa drugs.

























Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	
Distal (20 Ga.)	0.3	1013	
Medial (22 Ga.)	0.3	370	
Proximal (22 Ga.)	0.4	442	

<sup>\*</sup> Priming volumes are approximate and are done without accessories.



EU Authorized Representative and Importer:




Teleflex Medical IDA Business and Technology Park Dublin Road, Athlone 2797 Co. Westmeath, Ireland

All components are CE 2797 unless otherwise noted.

Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA

Product of xxx Packaged in xxx







(01)XXXXXXXXXXXXXXX (11)YYMMDD (10)LotNumber

)feleflex® www.teleflex.com

LBL055031 R01 (2024-04)



**REF** CS-26553

.018 inch dia. spring-wire guide





<sup>†</sup> Flow rate values are approximate and are determined using deionized water at 100 cm head height.