
ARRC





(IPNXXXXXX)

20 cm catheter length

.032 inch dia. spring-wire guide

Arrowg+ard Blue® Five-Lumen CVC

- Arrowg+ard Blue® Five-Lumen Catheter: 8.5 Fr. (3.0 mm OD) x 20 cm
- Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 23-5/8" (60 cm) (Straight Soft Tip on One End "J" Tip on Other) with Arrow
- Advancer with ECG Mark
 Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer Needle
- Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW Pressure Transduction Probe
- Arrow® Raulerson Spring-Wire Introduction Syringe: 5 mL Tissue Dilator: 9 Fr. (3.0 mm) x 10.2 cm

- Dust Cap: Non-Vented
 SecondSite™ Adjustable Hub: Fastener
 SecondSite™ Adjustable Hub: Catheter Clamp

All components are CE 2797 unless otherwise noted.

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU Not made with natural rubber latex.

Store below 25°C (77°F). Avoid excessive heat above 40°C (104°F). Fluid path components are non-pyrogenic.

Contraindications: The Arrowg+ard Blue antimicrobial catheter is contraindicated for patients with known hypersensitivity to chlorhexidine, silver sulfadiazine and/or sulfa drugs.







Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	
Distal (16 Ga.)	0.63	2689	
Medial 1 (14 Ga.)	0.78	4748	
Medial 2 (18 Ga.)	0.38	888	
Medial 3 (18 Ga.)	0.40	1013	
Proximal (18 Ga.)	0.42	988	

^{*} Priming volumes are approximate and are done without accessories. † Flow rate values are approximate and are determined using deionized water at 100 cm head height.



Technology Park Dublin Road, Athlone 2797 Co. Westmeath, Ireland

All components are CE 2797 unless otherwise noted.


Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA

Product of xxx Packaged in xxx

(01)XXXXXXXXXXXXXXX (11)YYMMDD (10)Lot Number

1feleflex® www.teleflex.com

LBL055043 R02 (2024-10)









20 cm catheter length

.032 inch dia. spring-wire guide



