PB-10005-000 Dimensions: Width: 6-3/4" (17,2 cm) Length: 11-5/16" (28,7 cm) T04200100A6 Dimensions: 6 5/8" x 10 1/2"

Product of XXX
Packaged in XXX

ARROW

CVC 3 LUMEN

REF CS-15853 (IPNXXXXXX)

8.5 Fr. **3** Lumen **20** cm catheter length **.032** inch dia. spring-wire guide

Three-Lumen CVC

Contents:

1: Three-Lumen Catheter: 8.5 Fr. (3.0 mm OD) x 20 cm
1: Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 23-5/8" (60 cm) (Straight Soft Tip on One End - "J" Tip on Other) with Arrow Advancer with ECG Mark
1: Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer Needle
1: Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW
1: Syringe: 5 mL Luer-Slip
1: Tissue Dilator: 9 Fr. (3.0 mm) x 10.2 cm
3: Dust Cap: Non-Vented
1: SecondSite™ Adjustable Hub: Fastener
1: SecondSite™ Adjustable Hub: Catheter Clamp

All components are CE 2797 unless otherwise noted.

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU

Not made with natural rubber latex.

Fluid path components are non-pyrogenic.

MD STERILE EO LATEX

CAS # 7440-48-4

en be bg hr cs da nl et fi fr de el hu is it lv lt no
pl pt ro ru sr sk sl es sv tr uk

Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)
Distal (16 Ga.)	0.47	2930
Medial (14 Ga.)	0.89	6267
Proximal (16 Ga.)	0.47	3731

* Priming volumes are approximate and are done without accessories.
† Flow rate values are approximate and are determined using deionized water at 100 cm head height.

EU Authorized Representative and Importer:
EC REP Teleflex Medical
IDA Business and Technology Park
Dublin Road, Athlone
Co. Westmeath, Ireland
CE 2797

Arrow International LLC
Subsidiary of Teleflex Incorporated
3015 Carrington Mill Blvd.
Morrisville, NC 27560 USA

Teleflex®
www.teleflex.com

LBL055444 R03 (2024-01)

LOT LotNumber

YYYY-MM-DD YYYY-MM-DD

(01)XXXXXXXXXXXXXX
(17)YYMMDD
(11)YYMMDD
(10)LotNumber

CVC 3 LUMEN
8.5 Fr. **3** Lumen **20** cm catheter length **.032** inch dia. spring-wire guide
REF CS-15853
Three-Lumen CVC
ARROW