Product of XXX Packaged in XXX





(IPNXXXXXX)

cm catheter length

1032 inch dia. spring-wire guide

ARRC

Three-Lumen CVC

- Three-Lumen Catheter: 7 Fr. (2.5 mm OD) x 30 cm Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 26-3/4" (68 cm) (Straight Soft Tip on One End "J" Tip on Other) with Arrow Advancer with ECG Mark
- Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer Needle
- Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW
- Syringe: 5 mL Luer-Slip Tissue Dilator: 8.5 Fr. (2.8 mm) x 10.2 cm
- Dust Cap: Non-Vented
 SecondSite™ Adjustable Hub: Fastener
 SecondSite™ Adjustable Hub: Catheter Clamp
- All components are CE 2797 unless otherwise noted

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU

Not made with natural rubber latex.

Fluid path components are non-pyrogenic.

$\overline{\dot{\mathbb{N}}}$	MD	[]i
		$\overline{}$





















Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	
Distal (16 Ga.) Medial (18 Ga.)	0.54 0.45	2025 896	
Proximal (18 Ga.)	0.48	955	



[†] Flow rate values are approximate and are determined using deionized water at 100 cm head height.




EU Authorized Representative and Importer:


Teleflex Medical EC REP IDA Business and E 2797 Technology Park Dublin Road, Athlone Co. Westmeath, Ireland

Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA











(01)XXXXXXXXXXXXXXX (11)YYMMDD (10)LotNumber

LBL055604 R01 (2024-03)



REF | CS-14703

30 cm catheter length

.032 inch dia. spring-wire guide



