

Dimensions:
Width: 8-3/4" (22,2 cm)
Length: 11-1/8" (28,3 cm)

PB-10001-000A
PBZ-10001-000A

T-12703-100C
Width: 8.7598 in = 222.5mm
Length: 10.374 in = 263.5mm

ARROW



REF EU-15802-CVET (IPNXXXXXX)

8 Fr. 2 Lumen 20 cm catheter length .032 inch dia. spring-wire guide

Two-Lumen CVC

Contents:

- 1: Two-Lumen Catheter: 8 Fr. (2.8 mm OD) x 20 cm
- 1: Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 23-5/8" (60 cm) (Straight Soft Tip on One End - "J" Tip on Other) with Arrow Advancer with ECG Mark
- 1: Introducer Needle: Echogenic 18 Ga. x 2-1/2" (6.35 cm) XTW
- 1: Pressure Transduction Probe
- 1: Arrow® Raulerson Spring-Wire Introduction Syringe: 5 mL
- 1: Tissue Dilator: 9 Fr. (3.0 mm) x 10.2 cm
- 1: ECG Extension Cable
- 2: Dust Cap: Non-Vented
- 1: SecondSite™ Adjustable Hub: Fastener
- 1: SecondSite™ Adjustable Hub: Catheter Clamp
- 1: Scalpel: #11


All components are CE 2797 unless otherwise noted.

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death.

www.teleflex.com/IFU

Not made with natural rubber latex.

Fluid path components are non-pyrogenic.



CAS # 7440-48-4



Lumen

Priming
Volume*
(mL)

Gravity
Flow
Rate†
(mL/hr)

Distal (14 Ga.)	0.74	5354
Proximal (14 Ga.)	0.81	4324

* Priming volumes are approximate and are done without accessories.

† Flow rate values are approximate and are determined using deionized water at 100 cm head height.



EU Authorized
Representative and
Importer:



Teleflex Medical
IDA Business and
Technology Park
Dublin Road, Athlone
Co. Westmeath, Ireland

All components are CE 2797 unless otherwise noted.

Arrow International LLC
Subsidiary of Teleflex Incorporated
3015 Carrington Mill Blvd.
Morrisville, NC 27560 USA

LOT Lot Number

YYYY-MM-DD

YYYY-MM-DD



(01)XXXXXXXXXXXXXX
(17)YYMMDD
(11)YYMMDD
(10)Lot Number

Product of xxx
Packaged in xxx

Teleflex®
www.teleflex.com

LBL055712 R03 (2025-01)



Two-Lumen CVC

REF EU-15802-CVET

8 Fr. 2 Lumen 20 cm catheter length .032 inch dia. spring-wire guide

ARROW