



## REF EU-15802-CVET

20 cm catheter length

## **Two-Lumen CVC**

- Two-Lumen Catheter: 8 Fr. (2.8 mm OD) x 20 cm
- Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 23-5/8" (60 cm) (Straight Soft Tip on One End "J" Tip on Other) with Arrow Advancer with ECG Mark Introducer Needle: Echogenic 18 Ga. x 2-1/2" (6.35 cm) XTW

- Pressure Transduction Probe
  Arrow® Raulerson Spring-Wire Introduction Syringe: 5 mL
  Tissue Dilator: 9 Fr. (3.0 mm) x 10.2 cm

- ECG Extension Cable
  Dust Cap: Non-Vented
- SecondSite™ Adjustable Hub: Fastener SecondSite™ Adjustable Hub: Catheter Clamp
- Scalpel: #11

All components are CE 2797 unless otherwise noted.

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU Not made with natural rubber latex.

Fluid path components are non-pyrogenic.



Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	
Distal (14 Ga.)	0.74	5354	
Proximal (14 Ga.)	0.81	4324	

<sup>\*</sup> Priming volumes are approximate and are done without accessories.



EU Authorized Representative and Importer:



Teleflex Medical IDA Business and Technology Park Dublin Road, Athlone Technology Park Dublin Road, Athlone 2797 Co. Westmeath, Ireland

Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA



LBL055712 R02 (2023-09)











<sup>†</sup> Flow rate values are approximate and are determined using deionized water at 100 cm head height.