



Four-Lumen CVC

Four-Lumen Catheter: 8.5 Fr. (3.0 mm OD) x 16 cm Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 23-5/8" (60 cm) (Straight Soft Tip on One End - "J" Tip on Other) with Arrow Advancer Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW Syringe: 5 mL Luer-Slip

Tissue Dilator: 9 Fr. (3.0 mm) x 10.2 cm

Dust Cap: Non-Vented
SecondSite™ Adjustable Hub: Fastener
SecondSite™ Adjustable Hub: Catheter Clamp All components are CE 2797 unless otherwise noted.


Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU Not made with natural rubber latex. Fluid path components are non-pyrogenic.







Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	
Distal (16 Ga.)	0.50	2756	
Medial 1 (14 Ga.)	0.60	5038	
Medial 2 (18 Ga.)	0.40	1386	
Proximal (18 Ga.)	0.40	1511	



† Flow rate values are approximate and are determined using deionized water at 100 cm head height.





EC REP IDA Business and Technology Park Dublin Road, Athlone 2797 Co. Westmeath, Ireland

All components are CE 2797 unless otherwise noted.


Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA


> Product of xxx Packaged in xxx


1feleflex® www.teleflex.com

(01)XXXXXXXXXXXXXXX (17)YYMMDD

(11)YYMMDD (10)Lot Number











LBL055715 R03 (2025-01)



Lumen

catheter length

spring-wire guide



Four-Lumen CVC

