



REF CV-12854


## Four-Lumen CVC

**Contents:**

- 1: Four-Lumen Catheter: 8.5 Fr. (3.0 mm OD) x 16 cm
- 1: Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 23-5/8" (60 cm) (Straight Soft Tip on One End - "J" Tip on Other) with Arrow Advancer
- 1: Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW
- 1: Syringe: 5 mL Luer-Slip
- 1: Tissue Dilator: 9 Fr. (3.0 mm) x 10.2 cm
- 4: Dust Cap: Non-Vented
- 1: SecondSite™ Adjustable Hub: Fastener
- 1: SecondSite™ Adjustable Hub: Catheter Clamp

All components are CE 2797 unless otherwise noted.

**Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. [www.teleflex.com/IFU](http://www.teleflex.com/IFU) Not made with natural rubber latex. Fluid path components are non-pyrogenic.**



Lumen

Priming  
Volume\*  
(mL)

Gravity  
Flow  
Rate†  
(mL/hr)

Distal (16 Ga.)	0.50	2756
Medial 1 (14 Ga.)	0.60	5038
Medial 2 (18 Ga.)	0.40	1386
Proximal (18 Ga.)	0.40	1511

\* Priming volumes are approximate and are done without accessories.

† Flow rate values are approximate and are determined using deionized water at 100 cm head height.



EU Authorized  
Representative and  
Importer:

EC REP

Teleflex Medical  
IDA Business and  
Technology Park  
Dublin Road, Athlone  
Co. Westmeath, Ireland  
2797



Arrow International LLC  
Subsidiary of Teleflex Incorporated  
3015 Carrington Mill Blvd.  
Morrisville, NC 27560 USA

**Teleflex®**  
[www.teleflex.com](http://www.teleflex.com)

LBL055715 R01 (2021-05)

LOT



8.5 Fr. 4 Lumen 16 cm catheter length .032 inch dia. spring-wire guide

REF CV-12854

Four-Lumen CVC