





60 cm catheter length .035 inch dia. spring-wire quide

## **Three-Lumen Antecubital CVC**

- Three-Lumen Catheter: 7 Fr. (2.5 mm OD) x 60 cm
- Spring-Wire Guide: .035" (0.89 mm) dia. x 39-1/2" (100 cm) PTFE-Coated (Straight Soft Tip on One End "J" Tip on Other) with Arrow Advancer Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer Needle
- Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW Pressure Transduction Probe
- Arrow® Raulerson Spring-Wire Introduction Syringe: 5 mL
- Tissue Dilator: 8.5 Fr. (2.8 mm) x 10.2 cm Dust Cap: Non-Vented

- SecondSite™ Adjustable Hub: Fastener SecondSite™ Adjustable Hub: Catheter Clamp
- Scalpel: #11
- Stopcock: 3-way

All components are CE 2797 unless otherwise noted.

Rx only

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU California Prop. 65

⚠ WARNING: Cancer and Reproductive Harm.

www.P65Warnings.ca.gov

Not made with natural rubber latex.

Fluid path components are non-pyrogenic.









































































Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	
Distal (16 Ga.)	0.80	1287	
Medial (18 Ga.)	0.60	409	
Provimal (18 Ca.)	0.62	416	

<sup>\*</sup> Priming volumes are approximate and are done without accessories.



EU Authorized Representative and Importer:



Teleflex Medical IDA Business and Technology Park Dublin Road, Athlone Technology Park Dublin Road, Athlone 2797 Co. Westmeath, Ireland

Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA



LBL055826 R02 (2023-10)



















<sup>\*\*</sup>Flow rate values are approximate and are determined using deionized water at 100 cm head height.