



(IPNXXXXXX)





30 cm catheter length

.032 inch dia. spring-wire guide

Four-Lumen CVC

- Four-Lumen Catheter: 8.5 Fr. (3.0 mm OD) x 30 cm Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 26-3/4" (68 cm) (Straight Soft Tip on One End "J" Tip on Other) with Arrow Advancer with ECG Mark Introducer Needle: Echogenic 18 Ga. x 2-1/2" (6.35 cm) XTW Syringe: 5 mt Luer-Slin

- Syringe: 5 mL Luer-Slip Tissue Dilator: 9 Fr. (3.0 mm) x 10.2 cm
- ECG Extension Cable

- Dust Cap: Non-Vented
 SecondSite™ Adjustable Hub: Fastener
 SecondSite™ Adjustable Hub: Catheter Clamp
- Scalpel: #11

All components are CE 2797 unless otherwise noted.

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU Not made with natural rubber latex.

Fluid path components are non-pyrogenic

Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	
Distal (16 Ga.)	0.51	1826	
Medial 1 (14 Ga.)	0.62	3303	
Medial 2 (18 Ga.)	0.41	830	
Proximal (18 Ga.)	0.44	863	

^{*} Priming volumes are approximate and are done without accessories




















(01)XXXXXXXXXXXXXXX (17)YYMMDD (11)YYMMDD (10)Lot Number

EU Authorized
Representative and Importer:

Teleflex Medical
IDA Business and
Technology Park
Dublin Road, Athlone
2797
Co. Westmeath, Ireland

All components are CE 2797 unless

Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA

Product of xxx Packaged in xxx

Teleflex®

LBL055863 R02 (2024-09) /



Four-Lumen CVC





8.5 Fr. 4 Lumen

30 cm catheter length

.032 inch dia. spring-wire guide

ARROW

[†] Flow rate values are approximate and are determined using deionized water at 100 cm head height.