Product of xxx Packaged in xxx



REF AK-04050-S

(IPNXXXXXX)

16 cm catheter length

.035 inch dia. spring-wire guide

Internal Jugular Puncture

- One-Lumen Catheter: 16 Ga. (1.8 mm OD) x 16 cm
- Spring-Wire Guide: .035" (0.89 mm) dia. x 12" (30 cm) (Straight Soft Tip on Both Ends)
 Catheter: 18 Ga. x 1-9/16" (3.97 cm) Radiopaque over 20 Ga. RW
- Introducer Needle
- Injection Needle: 25 Ga. x 1" (2.54 cm) Injection Needle: 22 Ga. x 1-1/2" (3.81 cm)
- Introducer Needle: 18 Ga. x 1-1/2" (3.81 cm) XTW Syringe: 3 mL Luer-Lock Tissue Dilator: 7 Fr. (2.3 mm) x 10.2 cm

- Drape: 18" x 26" (46 cm x 66 cm) with 3" (7.6 cm) fenestration
- Prep Sponge Swab
 Gauze Pad: 2" x 2" (5 cm x 5 cm)
- All components are CE 2797 unless otherwise noted.

Rx	only
----	------

Warning: Read all package insert warnings, precautions and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU Not made with natural rubber latex. Fluid path components are non-pyrogenic.

Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	
Distal (16 Ga.)	0.17	3245	

^{*} Priming volumes are approximate and are done without accessories.

















CAS # 7440-48-4



EU Authorized Representative and Importer:



Teleflex Medical IDA Business and Technology Park
Dublin Road, Athlone
7797 Co. Westmeath, Ireland

Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA



LBL055902 R01 (2024-01)

LOT Lot Number





(01)XXXXXXXXXXXXXXX (17)YYMMDD (11)YYMMDD (10)Lot Number

REF AK-04050-S







.035 inch dia. spring-wire guide



 $[\]dagger$ Flow rate values are approximate and are determined using deionized water at 100 cm head height.