ARRC

Product of xxx





(IPNXXXXXX)

20 cm catheter length

.032 inch dia. spring-wire quide

Arrowg+ard Blue Plus® Four-Lumen CVC

- Arrowg+ard Blue Plus®1 Four-Lumen Catheter: 8.5 Fr. (3.0 mm OD) x 20 cm
- Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 23-5/8" (60 cm) (Straight Soft Tip on One End "J" Tip on Other) with Arrow Advancer with ECG Mark
- Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW
 - Syringe: 5 mL Luer-Slip
 - Tissue Dilator: 9 Fr. (3.0 mm) x 10.2 cm Dust Cap: Non-Vented

- SecondSite™ Adjustable Hub: Fastener SecondSite™ Adjustable Hub: Catheter Clamp

¹Licensed under US Patent No. 7,329,412.

All components are CE 2797 unless otherwise noted.

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU Not made with natural rubber latex.

Store below 25°C (77°F). Avoid excessive heat above 40°C (104°F). Fluid path components are non-pyrogenic.

Contraindications: The Arrowg+ard Blue Plus antimicrobial catheter is contraindicated for patients with known hypersensitivity to chlorhexidine, silver sulfadiazine and/or sulfa drugs.



(<u>||</u>)CAS # 7440-48-4



Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	
Distal (16 Ga.)	0.40	2283	
Medial 1 (14 Ga.)	0.50	4316	
Medial 2 (18 Ga.)	0.36	1079	
Proximal (18 Ga.)	0.39	1162	

^{*} Priming volumes are approximate and are done without accessories.





Teleflex Medical EC REP IDA Business and Technology Park Dublin Road, Athlone Co. Westmeath, Ireland

Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA



LBL055914 R03 (2024-01)









(01)XXXXXXXXXXXXXXX (11)YYMMDD (10)Lot Number



REF CV-45854

20 cm catheter length

.032 inch dia. spring-wire guide



[†] Flow rate values are approximate and are determined using deionized water at 100 cm head