**ARRC** 

Product of xxx Packaged in xxx





(IPNXXXXXX)

20 cm catheter length

1032 inch dia. spring-wire guide

## Two-Lumen CVC

- Two-Lumen Catheter: 8 Fr. (2.8 mm OD) x 20 cm Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 23-5/8" (60 cm) (Straight Soft Tip on One End "J" Tip on Other) with Arrow Advancer with ECG Mark
- Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer Needle
- Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW
- Pressure Transduction Probe
  Arrow® Raulerson Spring-Wire Introduction Syringe: 5 mL

- Tissue Dilator: 9 Fr. (3.0 mm) x 10.2 cm

  Dust Cap: Non-Vented

  SecondSite™ Adjustable Hub: Fastener

  SecondSite™ Adjustable Hub: Catheter Clamp

All components are CE 2797 unless otherwise noted.

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU

Not made with natural rubber latex.

Fluid path components are non-pyrogenic





























Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	
Distal (14 Ga.)	0.74	5354	
Proximal (14 Ga.)	0.81	4324	

Priming volumes are approximate and are done without accessories. † Flow rate values are approximate and are determined using deionized water at 100 cm head height.

EU Authorized Representative and Importer:

Teleflex Medical EC REP IDA Business and E 2797 Technology Park Dublin Road, Athlone Co. Westmeath, Ireland

Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA

)feleflex®

LBL055981 R01 (2024-03)









(01)XXXXXXXXXXXXXXX (11)YYMMDD (10)LotNumber



20 cm catheter length

.032 inch dia. spring-wire guide



