



**REF CV-50014-BF**



## One-Lumen CVC

**Contents:**

- 1: One-Lumen Catheter: 14 Ga. (2.2 mm OD) x 20 cm, Side Holes
- 1: Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - "J" Tip on Other) with Arrow Advancer
- 1: Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW
- 1: Syringe: 5 mL Luer-Slip
- 1: Tissue Dilator: 7 Fr. (2.3 mm) x 10.2 cm
- 1: SecondSite™ Adjustable Hub: Fastener
- 1: SecondSite™ Adjustable Hub: Catheter Clamp

All components are CE 2797 unless otherwise noted.

**Rx only Warning:** Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. [www.teleflex.com/IFU](http://www.teleflex.com/IFU) Not made with natural rubber latex. Fluid path components are non-pyrogenic.



Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)
Distal (14 Ga.)	0.4	6889

\* Priming volumes are approximate and are done without accessories.  
 † Flow rate values are approximate and are determined using deionized water at 100 cm head height.

CAS # 7440-48-4

EU Authorized Representative and Importer:

Teleflex Medical  
 IDA Business and  
 Technology Park  
 Dublin Road, Athlone  
 Co. Westmeath, Ireland

Arrow International LLC  
 Subsidiary of Teleflex Incorporated  
 3015 Carrington Mill Blvd.  
 Morrisville, NC 27560 USA

**Teleflex®**  
[www.teleflex.com](http://www.teleflex.com)

LBL056237 R01 (2023-11)

**LOT**



**14** Ga. **1** Lumen **20** cm catheter length **.032** inch dia. spring-wire guide

**REF CV-50014-BF**

## One-Lumen CVC