



₋umen CVC


- One-Lumen Catheter: 14 Ga. (2.2 mm OD) x 20 cm, Side Holes Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End "J" Tip on Other) with Arrow Advancer
- Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW
- Syringe: 5 mL Luer-Slip

 Tissue Dilator: 7 Fr. (2.3 mm) x 10.2 cm

 SecondSite™ Adjustable Hub: Fastener

 SecondSite™ Adjustable Hub: Catheter Clamp
- All components are CE 2797 unless otherwise noted.

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU Not made with natural rubber latex. Fluid path components are non-pyrogenic.







Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)
Distal (14 Ga.)	0.4	6889

* Priming volumes are approximate and are done without accessories. † Flow rate values are approximate and are determined using deionized water at 100 cm head





EC REP IDA Business and Technology Park Dublin Road, Athlone 2797 Co. Westmeath, Ireland

All components are CE 2797 unless otherwise noted.

Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA


> Product of xxx Packaged in xxx

1feleflex® www.teleflex.com

(01)XXXXXXXXXXXXXXX

(17)YYMMDD (11)YYMMDD (10)Lot Number

LBL056238 R03 (2024-12)











Lumen

catheter

\$\$\ \text{1032} \ \text{spring-wire} \ \text{guide}



One-Lumen CVC

