



(IPNXXXXXX)

40 cm catheter length .018 inch dia. spring-wire guide

ARROW

Pressure Injectable Two-Lumen PICC

Two Lumen Catheter: 5 Fr. (1.81 mm OD) x 40 cm, Pressure Injectable, T-Port Connector, Blue FlexTip®, Contamination Guard

and Placement Wire
GlideThru™ Peel-Away Sheath: 5 Fr. x 2-3/4" (7 cm) Radiopaque over 5 Fr. Dilator

Spring-Wire Guide, Nitinol, Marked: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - Straight Stiff Tip on

Spring-virle Guide, Nitifilor, Marked. 3.16 (0.46 min) dia. x 17. Other) with Arrow Advancer Injection Needle: Eclipse™1 25 Ga. x 1" (2.54 cm) Injection Needle: Eclipse™1 25 Ga. x 1" (2.54 cm) RW Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW Filter Needle: 18 Ga. TW x 1-1/2" (3.81 cm) with Blunt Fill Tip

Syringe: 10 mL Luer-Lock

Syringe: 3 mL Luer-Lock
Syringe: 3 mL Luer-Lock
SecondSite™ Adjustable Hub: Fastener
SecondSite™ Adjustable Hub: Catheter Clamp

SharpsAway® II Locking Disposal Cup SharpsAway® Disposal Cup

Catheter Trimmer

Towel: 24" x 36" (61 cm x 91 cm) Drape: 60" x 76" (152 cm x 193 cm)

Drape: 36" x 41" (91 cm x 104 cm) with 3" x 5" (8 cm x 13 cm) fenestration

Towel Safety Scalpel: #11

Patient ID Card

Sterile Procedure Sign Patient Information Booklet Chart Sticker

PICC Line Insertion Checklist

Paper Tape Measure Tourniquet

Gauze Pad: 2" x 2" (5 cm x 5 cm)

Gauze Pad: 4" x 4" (10 cm x 10 cm)

Dressing: Tegaderm®² I.V. Advanced 3-1/4" x 4-1/2" (8.5 cm x 11.5 cm)

Dressing: GRIP-LOK®³ Catheter Fixation Device

Surgical Apparel: Cap
Surgical Apparel: Impervious Gown
Dressing: Steri-Strip®2 1/2" x 4" (1.2 cm x 10 cm)

Surgical Apparel: Mask
Surgical Apparel: Mask with Shield
Transducer Cover: 4-12/16" x 95" (12 cm x 244 cm)
Valve: MicroCLAVE™4 Neutral Displacement Connector
HemoHopper® Fluid Receptacle

¹A trademark of Becton, Dickinson and Company ²A registered trademark of 3M Company.

³A registered trademark of TIDI.

⁴A trademark of ICU Medical, Inc.
All components are CE 2797 unless otherwise noted.

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU

Not made with natural rubber latex. Fluid path components are non-pyrogenic

Contraindications: The Pressure Injectable PICC is contraindicated wherever there is presence of device related infections or presence of thrombosis in the intended insertion vessel or catheter pathway. Clinical assessment of the patient must be completed to ensure no

Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	Pump Flow Rate†† (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (18 Ga.)	0.36	416	3500	4
Proximal (18 Ga.)	0.38	475	4090	4

* Priming volumes are approximate and are done without accessories. † Flow rate values are approximate and are determined using deionized water at 100 cm head

†† Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.

** Pressure injection flow rates are determined at the injector pressure setting of 300 psi maximum using media of 11.8 centipoise viscosity, with 152 cm pressure tubing.



EU Authorized Representative and

Teleflex Medical IDA Business and Technology Park
Dublin Road, Athlone
2797 Co. Westmeath, Ireland All components are CE 2797 unless otherwise noted.

Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA

Product of xxx Packaged in xxx

Teleflex® LBL056501 R04 (2025-01)





STERILE EO



(01)XXXXXXXXXXXXXXX (10)Lot Number









