## Seal/Weld Area

Width: 272 mm Length: 365 mm Width: 10.7087" Length: 14.3701"

.018 inch dia. spring-wire guide



REF PR-05541-HPX (IPNXXXXXX) **4**<sup>Fr.</sup> **1**<sup>Lumen</sup> 55<sup>cm</sup> catheter length

## **Pressure Injectable One-Lumen PICC with 130 cm Wire**

## Contents

- origin:xxxxxxxxxxxxxxxxxxxxxxxx

- Catheter Trimmer origin:xxxxxxxxxxxxxxxxxxxxxxxxxxx
- Towel: 24" x 36" (61 cm x 91 cm) origin:xxxxxxxxxxxxxxxxxxxxx 1:

## Rx only

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death.

Injury or death. California Prop. 65 A WARNING: Cancer and Reproductive Harm. www.P65Warnings.ca.gov Not made with natural rubber latex. Store between 20 – 25°C (68 – 77°F).

Sterilized using ethylene oxide unless otherwise indicated in the contents list.

Fluid path components are non-pyrogenic.

Arrow International provides the enclosed medication label(s) for your convenience. Please ensure that these labels are applied to the correct syringe and corresponding medication. **Contraindications: The Pressure Injectable PICC is contraindicated** 

wherever there is presence of device related infections or presence of thrombosis in the intended insertion vessel or catheter pathway. Clinical assessment of the patient must be completed to ensure no contraindications exist.

- 10

- <sup>1</sup>A trademark of Becton, Dickinson and Company
- <sup>2</sup>A registered trademark of CareFusion or one of its subsidiaries. <sup>3</sup>A registered trademark of Johnson & Johnson Corporation.
- <sup>4</sup>A registered trademark of C. R. Bard, Inc.

4<sup>Fr.</sup> 1<sup>Lumen</sup>

- <sup>5</sup>A registered trademark of 3M Company
  - MAX Pressure Injection Flow Rate\*\* (mL/sec) Gravity Flow Rate† (mL/hr) Pump Flow Rate†† (mL/hr) Volume (mL) Distal (18 Ga.) 0.48 436 4075

ARROW

\* Priming volumes are approximate and are done without accessories.
† Flow rate values are approximate and are determined using deionized water at 100 cm head height.

++ Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities. approximate now capaonines. \*\* Pressure injection flow rates are determined at the injector pressure setting of 300 psi maximum using media of 11.8 centipoise viscosity, with 152 cm pressure tubing.

**REF PR-05541-HPX** 

LOT LotNumber M YYYY-MM-DD C YYYY-MM-DD



Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA

.018 inch dia. spring-wire guide

ARROW

Set Product of xxx Packaged in xxx

55 catheter length



**Pressure Injectable One-Lumen PICC with 130** cm Wire