

16 Ga. 2 Lumen

50 cm catheter length .018 inch dia. spring-wire quide

Two-Lumen PICC with 130 cm Wire

- Two Lumen Catheter: 16 Ga. (1.76 mm OD) x 50 cm, Blue FlexTip®
- GlideThru[™] Peel-Away Sheath: 5 Fr. x 4" (10 cm) Radiopaque over 5 Fr. Dilator Spring-Wire Guide: 0.18" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on Both Ends) Spring-Wire Guide, Marked: .018" (0.46 mm) dia. x 51-3/16" (130 cm)(Straight Soft Tip on
- One End Straight Stiff Tip on Other)
 Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- Syringe: 5 mL Luer-Slip

- Dust Cap: Non-Vented
 SecondSite™ Adjustable Hub: Fastener
 SecondSite™ Adjustable Hub: Catheter Clamp
- Patient ID Card
- Chart Sticker
- Patient Information Booklet
- Paper Tape Measure
- Dressing: STATLOCK®¹ PICC Plus Catheter Stabilization Device

¹A registered trademark of C. R. Bard, Inc.

Rx only

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU California Prop. 65

⚠ WARNING: Cancer and Reproductive Harm.

www.P65Warnings.ca.gov

Not made with natural rubber latex.

Fluid path components are non-pyrogenic.

Contraindications: The PICC is contraindicated wherever there is presence of device related infections or presence of thrombosis in the intended insertion vessel or catheter pathway. Clinical assessment of the patient must be completed to ensure no contraindications exist.
























^{*} Priming volumes are approximate and are done without accessories.







Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA



LBL056602 R01 (2023-02)

ARRON



Two-Lumen PICC with 130 cm Wire







[†] Flow rate values are approximate and are determined using deionized water at 100 cm head height.

^{††} Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.