



**REF AJ-01671** 

70 cm catheter length

■035 inch dia. spring-wire guide

## **One-Lumen PICC Set**

- One Lumen Catheter: 16 Ga. (1.80 mm OD) x 70 cm, Side Holes, Blue FlexTip®, Contamination Guard
- Spring-Wire Guide: .035" (0.89 mm) dia. x 39-1/2" (100 cm) PTFE-Coated (Straight Soft Tip on One End "J" Tip on Other) with Arrow Advancer Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer Needle
- Pressure Transduction Probe
- Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW and 5 mL Arrow® Raulerson Spring-Wire Introduction Syringe
  Tissue Dilator: 7 Fr. (2.3 mm) x 10.2 cm

- Dust Cap: Non-Vented
  SecondSite™ Adjustable Hub: Fastener
- SecondSite™ Adjustable Hub: Catheter Clamp
- Scalpel: #11
- Stopcock: 3-way

## Rx only

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death.

Not made with natural rubber latex.

Sterilized using ethylene oxide unless otherwise indicated in the contents list.

Fluid path components are non-pyrogenic.

Contraindications: The PICC is contraindicated wherever there is presence of device related infections or presence of thrombosis in the intended insertion vessel or catheter pathway. Clinical assessment of the patient must be completed to ensure no contraindications exist.


























<sup>\*</sup> Priming volumes are approximate and are done without accessories.







Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA



LBL056611 R00 (2021-10)



**One-Lumen PICC Set** 





 $<sup>\</sup>dagger$  Flow rate values are approximate and are determined using deionized water at 100 cm head height.

<sup>††</sup> Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.