
ARROW/





(IPNXXXXXX)

50 cm catheter length .018 inch dia. spring-wire quide

## One-Lumen PICC with 130 cm Wire

- GlideThru™ Peel-Away Sheath: 4 Fr. x 4" (10 cm) Radiopaque over 4 Fr. Dilator
- origin:xxxxxxxxxxxxxxxxxxxxxxxxxxxxx
- Spring-Wire Guide: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on Both Ends) origin:xxxxxxxxxxxxxxxxxxxxxxxx
- Spring-Wire Guide, Marked: .018" (0.46 mm) dia. x 51-3/16" (130 cm)(Straight Soft Tip on One End -Straight Stiff Tip on Other) origin:xxxxxxxxxxxxxxxxxxxxxxxxx

- <sup>1</sup>A registered trademark of C. R. Bard, Inc.

Rx only

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death.

California Prop. 65

www.teleflex.com/IFU

⚠ WARNING: Cancer and Reproductive Harm.

www.P65Warnings.ca.gov

Not made with natural rubber latex.

Fluid path components are non-pyrogenic.

Contraindications: The PICC is contraindicated wherever there is presence of device related infections or presence of thrombosis in the intended insertion vessel or catheter pathway. Clinical assessment of the patient must be completed to ensure no contraindications exist.






















<sup>\*</sup> Priming volumes are approximate and are done without accessories.


Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA

Set Product of xxx Packaged in xxx

7feleflex®

LBL056613 R02 (2024-05)

LOT Lot Number S YYYY-MM-DD





(17)YYMMDD (11)YYMMDD

One-Lumen PICC with 130 cm Wire

**ARROW** 



50 cm catheter length 1018 inch dia. spring-wire guide

<sup>†</sup> Flow rate values are approximate and are determined using deionized water at 100 cm head

<sup>††</sup> Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.