

Dimensions:  
 Width: 8-3/4" (22,2 cm)  
 Length: 11-1/8" (28,3 cm)

**PB-10001-000A**  
**PBZ-10001-000A**

T-12703-100C  
 Width: 8.7598 in = 222.5mm  
 Length: 10.374 in = 263.5mm

Product of xxx  
 Packaged in xxx

**ARROW**



REF **PR-34041-HPSM** (IPNXXXXXX)

**4** Fr. **1** Lumen **40** cm catheter length **.018** inch dia. spring-wire guide

# Pressure Injectable One-Lumen PICC with 80 cm Wire

## Contents:

- 1: One Lumen TaperFree® Catheter: 4 Fr. (1.45 mm OD) x 40 cm, Pressure Injectable, Blue FlexTip®
- 1: GlideThru™ Peel-Away Sheath: 4 Fr. x 4" (10 cm) Radiopaque over 4 Fr. Dilator
- 1: Spring-Wire Guide: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on Both Ends)
- 1: Spring-Wire Guide, Marked: .018" (0.46 mm) dia. x 31-1/2" (80 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other)
- 1: Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- 1: Syringe: 5 mL Luer-Lock
- 1: Dust Cap: Non-Vented
- 1: SecondSite™ Adjustable Hub: Catheter Clamp
- 1: SecondSite™ Adjustable Hub: Fastener
- 1: Patient ID Card
- 1: Chart Sticker
- 1: Patient Information Booklet
- 1: Checklist/CLIP Sheet
- 1: Paper Tape Measure
- 1: Dressing: STATLOCK®<sup>1</sup> PICC Plus Catheter Stabilization Device

<sup>1</sup>A registered trademark of C. R. Bard, Inc.

## Rx only

**Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU California Prop. 65**

**⚠ WARNING:** Cancer and Reproductive Harm.  
 www.P65Warnings.ca.gov

**Not made with natural rubber latex.**

Fluid path components are non-pyrogenic.

**Contraindications: The Pressure Injectable PICC is contraindicated wherever there is presence of device related infections or presence of thrombosis in the intended insertion vessel or catheter pathway. Clinical assessment of the patient must be completed to ensure no contraindications exist.**



Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	Pump Flow Rate‡ (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (17 Ga.)	0.49	1204	6520	5

\* Priming volumes are approximate and are done without accessories.

† Flow rate values are approximate and are determined using deionized water at 100 cm head height.

‡ Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.

\*\* Pressure injection flow rates are determined at the injector pressure setting of 300 psi maximum using media of 11.8 centipoise viscosity, with 152 cm pressure tubing.

**LOT** LotNumber

YYYY-MM-DD

YYYY-MM-DD



(01)XXXXXXXXXXXXXX  
 (17)YYMMDD  
 (11)YYMMDD  
 (10)LotNumber

Arrow International LLC  
 Subsidiary of Teleflex Incorporated  
 3015 Carrington Mill Blvd.  
 Morrisville, NC 27560 USA

**Teleflex**  
 www.teleflex.com

LBL056614 R01 (2024-03)



# Pressure Injectable One-Lumen PICC with 80 cm Wire

**ARROW**

REF **PR-34041-HPSM**

**4** Fr. **1** Lumen **40** cm catheter length **.018** inch dia. spring-wire guide