



REF EU-24041-IR

4 Fr. 1 Lumen 40 cm catheter length .018 inch dia. spring-wire guide

Pressure Injectable One-Lumen PICC

Contents:

- 1: One Lumen Catheter: 4 Fr. (1.45 mm OD) x 40 cm, Pressure Injectable, Blue FlexTip®
- 1: GlideThru™ Peel-Away Sheath: 4 Fr. x 2-3/4" (7 cm) Radiopaque over 4 Fr. Dilator
- 1: Spring-Wire Guide: .018" (0.46 mm) dia. x 13-1/8" (33 cm) (Straight Soft Tip on Both Ends)
- 1: Spring-Wire Guide, Marked: .018" (0.46 mm) dia. x 51-3/16" (130 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other)
- 1: Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- 1: Syringe: 10 mL Luer-Lock
- 1: SecondSite™ Adjustable Hub: Catheter Clamp
- 1: SecondSite™ Adjustable Hub: Fastener
- 1: SharpsAway® II Locking Disposal Cup
- 1: Catheter Trimmer
- 1: Safety Scalpel: #11
- 1: Patient ID Card
- 1: Patient Information Booklet
- 1: Chart Sticker
- 1: Paper Tape Measure
- 1: Tourniquet
- 1: Dressing: GRIP-LOK®¹ Catheter Fixation Device
- 1: Valve: MicroCLAVE™² Neutral Displacement Connector

¹A registered trademark of TIDI.
²A trademark of ICU Medical, Inc.
All components are CE 2797 unless otherwise noted.

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU

Not made with natural rubber latex.

Fluid path components are non-pyrogenic.

Contraindications: The Pressure Injectable PICC is contraindicated wherever there is presence of device related infections or presence of thrombosis in the intended insertion vessel or catheter pathway.

Clinical assessment of the patient must be completed to ensure no contraindications exist.

Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	Pump Flow Rate†† (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (18 Ga.)	0.38	847	4679	4

* Priming volumes are approximate and are done without accessories.

† Flow rate values are approximate and are determined using deionized water at 100 cm head height.

†† Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.

** Pressure injection flow rates are determined at the injector pressure setting of 300 psi maximum using media of 11.8 centipoise viscosity, with 152 cm pressure tubing.

- en
- cs
- nl
- fr
- de
- el
- it
- lt
- pl
- pt
- es
- sv
- tr



CAS # 7440-48-4



EU Authorized Representative and Importer:
Teleflex Medical
 IDA Business and Technology Park
 Dublin Road, Athlone
 Co. Westmeath, Ireland

Arrow International LLC
 Subsidiary of Teleflex Incorporated
 3015 Carrington Mill Blvd.
 Morrisville, NC 27560 USA

Teleflex®
www.teleflex.com
 LBL056787 R01 (2023-09)



REF EU-24041-IR

4 Fr. 1 Lumen 40 cm catheter length .018 inch dia. spring-wire guide

Pressure Injectable One-Lumen PICC