
ARRC

Product of xxx





(IPNXXXXXX)

16 cm catheter length

.032 inch dia. spring-wire guide

Arrowg+ard Blue® Four-Lumen CVC

Arrowg+ard Blue® Four-Lumen Catheter: 8.5 Fr. (3.0 mm OD) x 16 cm

Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - "J" Tip on Other) with Arrow Advancer Pressure Transduction Probe

Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW and 5 mL Arrow® Raulerson Spring-Wire Introduction Syringe Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW

Introducer Needle with 5 mL Luer-Slip Syringe Tissue Dilator: 10 Fr. (3.5 mm) x 10.2 cm

Dust Cap: Non-Vented
SecondSite™ Adjustable Hub: Fastener

SecondSite™ Adjustable Hub: Catheter Clamp

All components are CE 2797 unless otherwise noted.

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU

California Prop. 65

▲ WARNING: Cancer and Reproductive Harm www.P65Warnings.ca.gov

Not made with natural rubber latex.

Store below 25°C (77°F). Avoid excessive heat above 40°C (104°F). Fluid path components are non-pyrogenic

Contraindications: The Arrowg+ard Blue antimicrobial catheter is contraindicated for patients with known hypersensitivity to chlorhexidine, silver sulfadiazine and/or sulfa drugs.





Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	
Distal (16 Ga.)	0.40	2415	
Medial 1 (14 Ga.)	0.48	4723	
Medial 2 (18 Ga.)	0.37	1311	
Proximal (18 Ga.)	0.39	1403	

^{*} Priming volumes are approximate and are done without accessories.




EC REP IDA Business and Technology Park Dublin Road, Athlone Co. Westmeath, Ireland

Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA



LOT Lot Number







(01)XXXXXXXXXXXXXXX (11)YYMMDD (10)Lot Number

LBL056823 R01 (2024-01)



16 cm catheter length

.032 inch dia. spring-wire guide





[†] Flow rate values are approximate and are determined using deionized water at 100 cm head