**ARR**(





(IPNXXXXXX)

5 cm catheter length

■018 inch dia. spring-wire guide



- Three-Lumen Catheter: 5.5 Fr. (1.9 mm OD) x 5 cm
- Spring-Wire Guide: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End "J" Tip on Other)
- Catheter: 22 Ga. x 1-3/4" (4.45 cm) Radiopaque over 25 Ga. RW Introducer Needle
- Introducer Needle: 21 Ga. x 1-1/2" (3.81 cm) TW
- Syringe: 5 mL Luer-Slip
  Tissue Dilator: 6 Fr. (2.0 mm) x 7.6 cm
  Tissue Dilator: 6 Fr. (2.0 mm) x 4.1 cm
- Dust Cap: Non-Vented

All components are CE 2797 unless otherwise noted.

Rx only

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU

California Prop. 65

▲ WARNING: Cancer and Reproductive Harm.

www.P65Warnings.ca.gov

Not made with natural rubber latex.

Fluid path components are non-pyrogenic.





















Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	
Distal (20 Ga.)	0.37	1660	
Medial (22 Ga.)	0.30	1162	
Proximal (22 Ga.)	0.33	1162	

<sup>\*</sup> Priming volumes are approximate and are done without accessories.



EU Authorized Representative and Importer:



Teleflex Medical IDA Business and Technology Park Dublin Road, Athlone 2797 Co. Westmeath, Ireland

All components are CE 2797 unless otherwise noted.

Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA

Product of xxx Packaged in xxx





(01)XXXXXXXXXXXXXXX (17)YYMMDD (11)YYMMDD (10)Lot Number

1feleflex® www.teleflex.com

LBL056840 R02 (2024-09)



.018 inch dia. spring-wire guide







REF CS-12553-J

**LOT** Lot Number

<sup>†</sup> Flow rate values are approximate and are determined using deionized water at 100 cm head height.