**ARRC** 

Product of xxx Packaged in xxx





(IPNXXXXXX)

50 cm catheter length

## Two-Lumen PICC

- Two Lumen Catheter: 4 Fr. (1.45 mm OD) x 50 cm, Blue FlexTip® GlideThru™ Peel-Away Sheath: 4 Fr. x 4" (10 cm) Radiopaque over 4 Fr Dilator
- Spring-Wire Guide: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other) Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- Syringe: 5 mL Luer-Slip
- Dust Cap: Non-Vented SecondSite™ Adjustable Hub: Catheter Clamp SecondSite™ Adjustable Hub: Fastener
- Chart Sticker
- Patient Information Booklet
- Patient ID Card
- Paper Tape Measure
- Dressing: STATLOCK®¹ Catheter Stabilization Device
- <sup>1</sup>A registered trademark of C. R. Bard, Inc.

All components are CE 2797 unless otherwise noted.

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU

California Prop. 65

▲ WARNING: Cancer and Reproductive Harm.

www.P65Warnings.ca.gov

Not made with natural rubber latex. Fluid path components are non-pyrogenic.

Contraindications: The PICC is contraindicated wherever there is presence of device related infections or presence of thrombosis in the intended insertion vessel or catheter pathway. Clinical assessment of the patient must be completed to ensure no contraindications exist.


















Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	Pump Flow Rate†† (mL/hr)	
Distal (22 Ga.)	0.27	165	1446	
Proximal (22 Ga.)	0.33	139	1529	

Priming volumes are approximate and are done without accessories.



EU Authorized Representative and Importer:


Teleflex Medical EC REP IDA Business and Technology Park Dublin Road, Athlone Co. Westmeath, Ireland

Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA



LBL056842 R02 (2024-01)







(01)XXXXXXXXXXXXXXX (11)YYMMDD (10)Lot Number



REF PR-05042

50 cm catheter length

.018 inch dia. spring-wire guide





<sup>†</sup> Flow rate values are approximate and are determined using deionized water at 100 cm head height.

<sup>††</sup> Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.