



REF EU-04730-N

(IPNXXXXXX)

14 Ga. 1 Lumen

30 cm catheter length

.032 inch dia. spring-wire guide

# One-Lumen CVC

## Contents:

- 1: One-Lumen Catheter: 14 Ga. (2.2 mm OD) x 30 cm, Side Holes
  - 1: Spring-Wire Guide, Nitinol, Marked: .032" (0.81 mm) dia. x 26-3/4" (68 cm) (Straight Soft Tip on One End - "J" Tip on Other) with Arrow Advancer with ECG mark
  - 1: Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW
  - 1: Syringe: 5 mL Luer-Slip
  - 1: Tissue Dilator: 7 Fr. (2.3 mm) x 10.2 cm
  - 1: SecondSite™ Adjustable Hub: Fastener
  - 1: SecondSite™ Adjustable Hub: Catheter Clamp
- All components are CE 2797 unless otherwise noted.

**Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. [www.teleflex.com/IFU](http://www.teleflex.com/IFU)**  
**Not made with natural rubber latex.**  
 Fluid path components are non-pyrogenic.



CAS # 7440-48-4



Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)
Distal (14 Ga.)	0.72	5619

\* Priming volumes are approximate and are done without accessories.

† Flow rate values are approximate and are determined using deionized water at 100 cm head height.



EU Authorized Representative and Importer:



Teleflex Medical  
 IDA Business and  
 Technology Park  
 Dublin Road, Athlone  
 Co. Westmeath, Ireland



All components are CE 2797 unless otherwise noted.

Arrow International LLC  
 Subsidiary of Teleflex Incorporated  
 3015 Carrington Mill Blvd.  
 Morrisville, NC 27560 USA

Product of xxx  
 Packaged in xxx

LOT Lot Number

YYYY-MM-DD

YYYY-MM-DD



(01)XXXXXXXXXXXXXXXXXX  
 (17)YYMMDD  
 (11)YYMMDD  
 (10)Lot Number

**Teleflex**  
[www.teleflex.com](http://www.teleflex.com)

LBL056963 R02 (2024-11)



14 Ga. 1 Lumen

30 cm catheter length

.032 inch dia. spring-wire guide

REF EU-04730-N

# One-Lumen CVC

