



REF AK-04650-E-S

24^{Ga.} 1^{Lumen}

9^{cm}
catheter
length

.018^{inch dia.}
spring-wire
guide

One-Lumen CVC

Contents:

- 1: One-Lumen Catheter: 24 Ga. (0.8 mm OD) x 9 cm
- 1: Spring-Wire Guide: .018" (0.46 mm) dia. x 13-3/4" (35 cm) (Straight Soft Tip on One End - "J" Tip on Other)
- 1: Introducer Needle: 21 Ga. x 1-1/2" (3.81 cm) TW
- 2: Syringe: 3 mL Luer-Lock
- 1: SecondSite™ Adjustable Hub: Catheter Clamp
- 1: Drape: 18" x 26" (46 cm x 66 cm) with 3" (7.6 cm) fenestration
- 1: Scalpel: #11
- 1: Prep Sponge Swab
- 3: Gauze Pad: 2" x 2" (5 cm x 5 cm)

All components are CE 2797 unless otherwise noted.

Rx only

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU
Not made with natural rubber latex.

Fluid path components are non-pyrogenic.



Lumen

Priming
Volume^{*}
(mL)

Gravity
Flow
Rate[†]
(mL/hr)


Lumen	Priming Volume [*] (mL)	Gravity Flow Rate [†] (mL/hr)
Distal (24 Ga.)	0.1	416

* Priming volumes are approximate and are done without accessories.

† Flow rate values are approximate and are determined using deionized water at 100 cm head height.



LOT



EU Authorized Representative and Importer:



Teleflex Medical
IDA Business and
Technology Park
Dublin Road, Athlone
Co. Westmeath, Ireland



Arrow International LLC
Subsidiary of Teleflex Incorporated
3015 Carrington Mill Blvd.
Morrisville, NC 27560 USA

Teleflex®
www.teleflex.com

LBL057119 R01 (2023-09)



REF AK-04650-E-S

24^{Ga.} 1^{Lumen}

9^{cm}
catheter
length

.018^{inch dia.}
spring-wire
guide

One-Lumen CVC