ARROW

REF **EU-16702-CVET**

7 Fr. **2** Lumen **20** cm catheter length **.032** inch dia. spring-wire guide

Two-Lumen CVC

Contents:

1: Two-Lumen Catheter: 7 Fr. (2.5 mm OD) x 20 cm
1: Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 23-5/8" (60 cm) (Straight Soft Tip on One End - "J" Tip on Other) with Arrow Advancer with ECG Mark
1: Introducer Needle: Echogenic 18 Ga. x 2-1/2" (6.35 cm) XTW
1: Pressure Transduction Probe
1: Arrow® Raulerson Spring-Wire Introduction Syringe: 5 mL
1: Tissue Dilator: 8.5 Fr. (2.8 mm) x 10.2 cm
1: ECG Extension Cable
1: Dust Cap: Non-Vented
1: SecondSite™ Adjustable Hub: Fastener
1: SecondSite™ Adjustable Hub: Catheter Clamp
1: Scalpel: #11

All components are CE 2797 unless otherwise noted.

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU
Not made with natural rubber latex.
Fluid path components are non-pyrogenic.

MD STERILE EO LATEX CAS # 7440-48-4

en be bg hr cs da nl et fi fr de el hu is it lv lt no pl pt ro ru sr sk sl es sv tr uk

Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)
Distal (16 Ga.)	0.47	2681
Proximal (16 Ga.)	0.52	3013

* Priming volumes are approximate and are done without accessories.
† Flow rate values are approximate and are determined using deionized water at 100 cm head height.

LOT

EU Authorized Representative and Importer:
EC REP Teleflex Medical
IDA Business and Technology Park
Dublin Road, Athlone
Co. Westmeath, Ireland
CE 2797

Arrow International LLC
Subsidiary of Teleflex Incorporated
3015 Carrington Mill Blvd.
Morrisville, NC 27560 USA

Teleflex®
www.teleflex.com

LBL057129 R01 (2023-09)

Two-Lumen CVC

ARROW

REF EU-16702-CVET 7 Fr. 2 Lumen 20 cm catheter length .032 inch dia. spring-wire guide