



CDC-45063-HPK1A

(IPNXXXXXX)

6 Fr.

3 Lumen

50 cm catheter length

.018 inch dia. spring-wire guide

ARROW®

ErgoPack®

# Pressure Injectable Arrowg+ard Blue Advance® Three-Lumen PICC

UDI



## Contents:

- |   |   |
|---|---|
| 1: Three Lumen TaperFree® Catheter with Arrowg+ard Blue Advance® Antimicrobial/Antithrombogenic Protection <sup>1</sup> : 6 Fr. (2.11 mm OD) x 50 cm, Pressure Injectable, T-Port Connector, Blue FlexTip® and Placement Wire | 1: Safety Scalpel: #11  |
| 1: GlideThru™ Peel-Away Sheath: 6 Fr. x 2-3/4" (7 cm) Radiopaque over 6 Fr. Dilator   | 1: Sterile Procedure Sign   |
| 1: Spring-Wire Guide, Nitinol, Marked: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other) with Arrow Advancer  | 1: Patient ID Card  |
| 1: Injection Needle: SafetyGlide™ <sup>2</sup> 25 Ga. x 5/8" (1.60 cm)  | 1: Chart Sticker  |
| 1: Safety Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW  | 1: Patient Information Booklet  |
| 1: Blunt Fill Needle: 18 Ga. x 1-1/2" (3.81 cm)   | 1: Medication Label: 1% Lidocaine   |
| 1: Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW   | 1: Checklist/CLIP Sheet   |
| 1: Syringe: 10 mL Luer-Lock   | 2: Paper Tape Measure   |
| 1: Syringe: 3 mL Luer-Lock  | 1: Tourniquet   |
| 2: 10 mL Luer-Lock Pre-Filled Saline Syringe  | 10: Gauze Pad: 2" x 2" (5 cm x 5 cm)  |
| 1: 5 mL 1% Lidocaine HCl Solution and Alcohol Prep  | 10: Gauze Pad: 4" x 4" (10 cm x 10 cm)                                      |
| 1: 3 mL Applicator 2% CHG and 70% IPA ChloraPrep® <sup>3</sup> One-Step Solution  | 1: Surgical Apparel: Impervious Gown  |
| 1: 3 mL Applicator 2% CHG and 70% IPA ChloraPrep® <sup>3</sup> One-Step Solution with Hi-Lite Orange™ Tint  | 1: Dressing: I.V. Advanced 8.5 cm x 11.5 cm                                 |
| 3: Dust Cap: Non-Vented   | 1: Dressing: BIOPATCH® <sup>4</sup>   |
| 1: SecondSite™ Adjustable Hub: Fastener   | 1: Surgical Apparel: Mask with Eye Shield                                   |
| 1: SecondSite™ Adjustable Hub: Catheter Clamp   | 1: Dressing: STATLOCK® <sup>5</sup> PICC Plus Catheter Stabilization Device |
| 1: SharpsAway® II Locking Disposal Cup  | 1: Surgical Apparel: Bouffant Cap   |
| 1: SharpsAway® Disposal Cup   | 1: Surgical Apparel: Mask   |
| 1: Catheter Trimmer   | 1: Tape: Steri-Strip® <sup>6</sup>  |
| 1: Towel: 24" x 36" (61 cm x 91 cm)   | 1: HemoHopper® Fluid Receptacle   |
| 1: Maximal Barrier Drape™ with two 13 cm (5") x 15 cm (6") fenestrations  |   |
| 1: Towel  |   |

<sup>1</sup>Licensed under US Patent No. 7,329,412.  
<sup>2</sup>A trademark of Becton, Dickinson and Company.  
<sup>3</sup>A registered trademark of CareFusion or one of its subsidiaries.  
<sup>4</sup>A registered trademark of Johnson & Johnson Corporation.  
<sup>5</sup>A registered trademark of C. R. Bard, Inc.  
<sup>6</sup>A registered trademark of 3M Company.

## Not made with natural rubber latex.

Store between 20 – 25°C (68 – 77°F).

Arrow International provides the enclosed medication label(s) for your convenience. Please ensure that these labels are applied to the correct syringe and corresponding medication.

## Contraindications: The Pressure Injectable Arrowg+ard Blue Advance antimicrobial/antithrombogenic catheter is contraindicated:

- for patients with known hypersensitivity to chlorhexidine
- in the presence of device related infection in the intended insertion vessel or catheter pathway
- in the presence of thrombosis in the intended insertion vessel or catheter pathway



Lumen

	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	Pump Flow Rate†† (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (18 Ga.)	0.57	930	5920	6
Medial (19 Ga.)	0.43	271	2370	not rated
Proximal (19 Ga.)	0.44	277	2390	not rated

\* Priming volumes are approximate and are done without accessories.

† Flow rate values are approximate and are determined using deionized water at 100 cm head height.

†† Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.

\*\* Pressure injection flow rates are determined at the injector pressure setting of 300 psi maximum using media of 11.8 centipoise viscosity, with 152 cm pressure tubing.

