





**REF CDC-42552-JX1A** 

(IPNXXXXXX)



## Pressure Injectable Arrowg+ard Blue Advance® Two-Lumen JACC



## Contents:

- 1: Two-Lumen TaperFree® Catheter with Arrowg+ard Blue Advance® Antimicrobial/Antithrombogenic Protection<sup>1</sup>: 5.5 Fr. (1.86 mm OD) x 25 cm,
- GlideThru™ Peel-Away Sheath: 5.5 Fr. x 2-3/4" (7 cm) Radiopaque over 5.5 Fr.
- Spring-Wire Guide, Nitinol, Marked: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other) with Arrow Advancer
- Catheter: 20 Ga. x 1-3/4" (4.50 cm) over 22 Ga. Safety Introducer Needle
- Injection Needle: Eclipse™2 25 Ga. x 1-1/2" (3.81 cm)
- Safety Introducer Needle: Echogenic 21 Ga, x 2-3/4" (7 cm) TW

- 5 mL 1% Lidocaine HCl Solution and Alcohol Prep
- 3 mL Applicator 2% CHG and 70% IPA ChloraPrep®3 One-Step Solution with

- SecondSite™ Adjustable Hub: Catheter Clamp

- Dressing: STATLOCK®5 CV Plus Catheter Stabilization Device

- Transducer Cover: 5" x 48" (13 cm x 122 cm) with Sterile Gel origin:xxxxxxxxxxxxxxxxxxxxxxxxxx
- <sup>1</sup>Licensed under US Patent No. 7.329.412.
- <sup>2</sup>A trademark of Becton, Dickinson and Company
- 3A registered trademark of CareFusion or one of its subsidiaries.
- <sup>4</sup>A registered trademark of Johnson & Johnson Corporation.

<sup>5</sup>A registered trademark of C. R. Bard, Inc.

## Not made with natural rubber latex.

Store between 20 - 25°C (68 - 77°F)

Arrow International provides the enclosed medication label(s) for your convenience. Please ensure that these labels are applied to the correct syringe and

Contraindications: The Arrowg+ard Blue Advance antimicrobial/antithrombogenic catheter is contraindicated for patients with known hypersensitivity to chlorhexidine.

Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	Pump Flow Rate†† (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (18 Ga.)	0.32	847	4900	5
Proximal (18 Ga.)	0.33	647	4840	5

<sup>\*</sup> Priming volumes are approximate and are done without accessories.

- † Flow rate values are approximate and are determined using deionized water at 100 cm head
- †† Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.
- \*\* Pressure injection flow rates are determined using media of 11.8 centipoise (cP) viscosity, with 152 cm administration set tubing.



LBL057465 R04 (2024-05)