ARROW

REF **PR-41552-BAS**

5.5 Fr. **2** Lumen **15** cm catheter length **.018** inch dia. spring-wire guide

Pressure Injectable Arrowg+ard Blue Advance® Two-Lumen Midline

Contents:

1: Two-Lumen TaperFree® Catheter with Arrowg+ard Blue Advance™ Antimicrobial/Antithrombogenic Protection[1]: 5.5 Fr. (1.9 mm OD) x 15 cm, Pressure Injectable, Blue FlexTip®
1: GlideThru™ Peel-Away Sheath: 5.5 Fr. x 2-3/4" (7 cm) Radiopaque over 5.5 Fr. Dilator
1: Spring-Wire Guide, Nitinol, Marked: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other)
1: Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
1: Syringe: 10 mL Luer-Lock
2: Dust Cap: Non-Vented
1: SecondSite™ Adjustable Hub: Fastener
1: SecondSite™ Adjustable Hub: Catheter Clamp
1: SharpsAway® Disposal Cup
1: SharpsAway® II Locking Disposal Cup
1: Catheter Trimmer
1: Safety Scalpel: #11
1: Patient ID Card
1: Patient Information Booklet
1: Paper Tape Measure
1: Dressing: STATLOCK®[2] Catheter Stabilization Device

[1]Licensed under US Patent No. 7,329,412.
[2]A registered trademark of C. R. Bard, Inc.

Rx only

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death.

California Prop. 65

⚠ **WARNING:** Cancer and Reproductive Harm.
www.P65Warnings.ca.gov

Not made with natural rubber latex.

Store below 25°C (77°F). Avoid excessive heat above 30°C (86°F).

Fluid path components are non-pyrogenic.

Contraindications: The Arrowg+ard Blue Advance Pressure Injectable Midline is contraindicated for patients with known hypersensitivity to chlorhexidine.

Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	Pump Flow Rate†† (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (18 Ga.)	0.27	1071	5860	5
Proximal (18 Ga.)	0.28	898	6060	not rated

* Priming volumes are approximate and are done without accessories.
† Flow rate values are approximate and are determined using deionized water at 100 cm head height.
†† Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.
** Pressure injection flow rates are determined using media of 11.8 centipoise (cP) viscosity, with 152 cm administration set tubing.

MD STERILE EO LATEX 25°C (77°F) LOT

Arrow International LLC
Subsidiary of Teleflex Incorporated
3015 Carrington Mill Blvd.
Morrisville, NC 27560 USA

Teleflex®
www.teleflex.com

LBL057533 R00 (2021-11)