

35 cm catheter length

Pressure Injectable Arrowg+ard Blue Advance® One-Lumen JACC with 80 cm Hydrophilic-Coated Nitinol Guidewire

- One-Lumen TaperFree® Catheter with Arrowg+ard Blue Advance® Antimicrobial/Antithrombogenic Protection1: 4.5 2A registered trademark of 3M Company Fr. (1.55 mm OD) x 35 cm, Pressure Injectable origin:xxxxxxxxxxxxxxxxxxxxxxxxxxxx
- GlideThru™ Peel-Away Sheath: 4.5 Fr. x 4" (10 cm) Radiopaque over 4.5 Fr. Dilator
- Spring-Wire Guide, Nitinol, Marked: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - Straight
- Guidewire, Marked: .018" (0.46 mm) dia. x 80 cm Hydrophilic-Coated Nitinol with Soft Tip Tungsten Coil (CE 0120)

¹Licensed under US Patent Nos. 6,706,024, 6,872,195 and 7,329,412.

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU

California Prop. 65

⚠ WARNING: Cancer and Reproductive Harm.

www.P65Warnings.ca.gov

Not made with natural rubber latex.

Store below 25°C (77°F). Avoid excessive heat above 30°C (86°F).

Sterilized using ethylene oxide unless otherwise indicated in the contents list.

Fluid path components are non-pyrogenic.

Contraindications: The Arrowg+ard Blue Advance antimicrobial/antithrombogenic catheter is contraindicated for patients with known hypersensitivity to chlorhexidine.

| Lumen | Priming Volume* (mL) | Gravity Flow Rate† (mL/hr) | Pump Flow Rate†† (mL/hr) | MAX Pressure Injection Flow Rate** (mL/sec) |
|-----------------|----------------------------|-------------------------------------|--------------------------------|------------------------------------------------------|
| Distal (17 Ga.) | 0.44 | 1337 | 5913 | 5 |

^{*} Priming volumes are approximate and are done without accessories.





Morrisville, NC 27560 USA Set Product of xxx

Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd.



Packaged in xxx







(17)YYMMDD (11)YYMMDD (10)LotNumber

[†] Flow rate values are approximate and are determined using deionized water at 100 cm head height.

^{††} Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.

** Pressure injection flow rates are determined using media of 11.8 centipoise (cP) viscosity, with 152 cm administration set tubing.