



REF PR-01351-MH



One-Lumen PICC with 80cm Wire

Contents:

- 1: One Lumen Catheter: 3 Fr. (1.03 mm OD) x 55 cm, Contamination
- Guard GlideThru™ Peel-Away Sheath: 3 Fr. x 2-3/4" (7 cm) Radiopaque 1: over 3 Fr. Dilator
- Spring Wire Guide Assembly: .016" (0.40 mm) dia. x 13-1/8" (33 cm) 1: Spring Wire Guide Assembly: JUT6 (J.40 mm) dia. x 13-178 (33 cm (Straight Soft Tip On Both Ends) Spring-Wire Guide, Marked: J018" (0.46 mm) dia. x 31-1/2" (80 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other) Catheter: 22 Ga. x 1-3/4" (4.45 cm) Radiopaque over 25 Ga. RW Introducer Needle
- 1:
- 1:
- Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW 1:
- Syringe: 5 mL Luer-Slip Dust Cap: Non-Vented
- 1:
- Catheter Trimmer 1:
- Patient ID Card
- Chart Sticker 1:
- 1: Patient Information Booklet 1: Paper Tape Measure

All components are CE 2797 unless otherwise noted.

Rx only

Warning: Read all package insert warnings, precautions and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU Not made with natural rubber latex.

Fluid path components are non-pyrogenic. Contraindications: The PICC is contraindicated wherever there is presence of device related infections or presence of thrombosis in the intended insertion vessel or catheter

pathway. Clinical assessment of the patient must be completed to ensure no contraindications exist.

| Lumen | Priming Volume* (mL) | Gravity Flow Rate† (mL/hr) | Pump Flow Rate†† (mL/hr) | |
|-----------------|----------------------------|-------------------------------------|--------------------------------|--|
| Distal (20 Ga.) | 0.30 | 103 | 1040 | |

* Priming volumes are approximate and are done without accessories. † Flow rate values are approximate and are determined using deionized water at 100 cm head height.

 $\uparrow\uparrow$ Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.

