



REF AW-14732

.032 inch dia. spring-wire guide


68 cm spring-wire guide

Marked Spring-Wire Guide with Arrow Advancer Maximum OD per ISO 11070 is 0.82 mm.

Contents:

- 1: Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 26-3/4" (68 cm) (Straight Soft Tip on One End - "J" Tip on Other) with Arrow Advancer

Rx only www.teleflex.com/IFU



LOT



EU Authorized Representative and Importer:

Teleflex Medical
IDA Business and Technology Park
Dublin Road, Athlone
2797 Co. Westmeath, Ireland

Arrow International LLC
Subsidiary of Teleflex Incorporated
3015 Carrington Mill Blvd.
Morrisville, NC 27560 USA

Teleflex®
www.teleflex.com

LBL060648 R02 (2023-04)



REF AW-14732

.032 inch dia. spring-wire guide

68 cm spring-wire guide

Marked Spring-Wire Guide with Arrow Advancer Maximum OD per ISO 11070 is 0.82 mm.

Contents:

- 1: Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 26-3/4" (68 cm) (Straight Soft Tip on One End - "J" Tip on Other) with Arrow Advancer

Rx only www.teleflex.com/IFU



LOT



EU Authorized Representative and Importer:

Teleflex Medical
IDA Business and Technology Park
Dublin Road, Athlone
2797 Co. Westmeath, Ireland

Arrow International LLC
Subsidiary of Teleflex Incorporated
3015 Carrington Mill Blvd.
Morrisville, NC 27560 USA

Teleflex®
www.teleflex.com

LBL060648 R02 (2023-04)