





## Nitinol Marked Spring-Wire Guide with Arrow<sup>®</sup> GlideWheel<sup>™</sup> Wire Advancer Maximum OD per ISO 11070 is 0.64 mm.

Contents:

Spring-Wire Guide, Nitinol, Marked: .025" (0.64 mm) dia. x 23-5/8" (60 cm) (Straight Soft Tip on One 1: End - "J" Tip on Other) with Arrow® GlideWheel™ Wire Advance

Rx only Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU

California Prop. 65

MARNING: Cancer and Reproductive Harm. www.P65Warnings.ca.gov

Not made with natural rubber latex. Fluid path components are non-pyrogenic

 $\sim$ 



Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA

**]feleflex®** www.teleflex.com

LBL061027 R00 (2022-02)







## Nitinol Marked Spring-Wire Guide with Arrow<sup>®</sup> GlideWheel<sup>™</sup> Wire Advancer Maximum OD per ISO 11070 is 0.64 mm.

Contents:

LOT

LOT

Spring-Wire Guide, Nitinol, Marked: .025" (0.64 mm) dia. x 23-5/8" (60 cm) (Straight Soft Tip on One 1: End - "J" Tip on Other) with Arrow® GlideWheel™ Wire Advancer

Rx only Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU California Prop. 65 A WARNING: Cancer and Reproductive Harm.

www.P65Warnings.ca.gov

Not made with natural rubber latex. Fluid path components are non-pyrogenic



Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd Morrisville, NC 27560 USA



LBL061027 R00 (2022-02)



 $\sim$