

20 cm catheter length

.018 inch dia. spring-wire guide

## **Arrow® Midline Kit**

## Contents:

- 1: Midline Catheter, Trimmable: 4 Fr. (1.4 mm OD) x 20 cm, T-Port Connector,
- Contamination Guard and Placement Wire GlideThru™ Peel-Away Sheath: 4 Fr. x 2-3/4" (7 cm) Radiopaque over 4 Fr. Dilator
- Spring-Wire Guide, Nitinol, Marked: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End Straight Stiff Tip on Other) with Arrow
- Advancer
  Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
  Syringe: 10 mL Luer-Lock
  SharpsAway® II Locking Disposal Cup
  Catheter Trimmer
  Safety Scalpel: #11
  Paper Tape Measure

- Tourniquet

  Dressing: GRIP-LOK®¹ Catheter Fixation Device

  Valve: MicroCLAVE™2 Neutral Displacement Connector

<sup>1</sup>A registered trademark of TIDI. <sup>2</sup>A trademark of ICU Medical, Inc.

All components are CE 2797 unless otherwise noted.

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU Not made with natural rubber latex. Fluid path components are non-pyrogenic.

Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	Pump Flow Rate†† (mL/hr)	
Distal (18 Ga.)	0.30	1403	7110	

<sup>††</sup> Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.





























Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA



LBL061063 R01 (2022-06)















<sup>\*</sup> Priming volumes are approximate and are done without accessories. † Flow rate values are approximate and are determined using deionized water at 100 cm head height.