



REF CS-24703-E

7 Fr. 3 Lumen 30 cm catheter length .032 inch dia. spring-wire guide

Arrowgard Blue® Three-Lumen CVC

Contents:

- 1: Arrowgard Blue® Three-Lumen Catheter: 7 Fr. (2.5 mm OD) x 30 cm
- 1: Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 26-3/4" (68 cm) (Straight Soft Tip on One End - "J" Tip on Other) with Arrow Advancer
- 1: Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer Needle
- 1: Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW
- 1: Pressure Transduction Probe
- 1: Arrow® Raulerson Spring-Wire Introduction Syringe: 5 mL
- 1: Tissue Dilator: 8.5 Fr. (2.8 mm) x 10.2 cm
- 3: Dust Cap: Non-Vented
- 1: SecondSite™ Adjustable Hub: Fastener
- 1: SecondSite™ Adjustable Hub: Catheter Clamp

All components are CE 2797 unless otherwise noted.

Rx only

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU

Not made with natural rubber latex.

Store below 25°C (77°F). Avoid excessive heat above 40°C (104°F). Fluid path components are non-pyrogenic.

Contraindications: The Arrowgard Blue antimicrobial catheter is contraindicated for patients with known hypersensitivity to chlorhexidine, silver sulfadiazine and/or sulfa drugs.



Lumen


Priming Volume* (mL)

Gravity Flow Rate† (mL/hr)

Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)
Distal (16 Ga.)	0.6	2025
Medial (18 Ga.)	0.5	921
Proximal (18 Ga.)	0.5	1004

* Priming volumes are approximate and are done without accessories.

† Flow rate values are approximate and are determined using deionized water at 100 cm head height.



LOT



EU Authorized Representative and Importer:

EC REP Teleflex Medical
IDA Business and
Technology Park
Dublin Road, Athlone
2797 Co. Westmeath, Ireland

Arrow International LLC
Subsidiary of Teleflex Incorporated
3015 Carrington Mill Blvd.
Morrisville, NC 27560 USA

Teleflex®
www.teleflex.com

LBL061179 R03 (2023-11)



REF CS-24703-E

7 Fr. 3 Lumen 30 cm catheter length .032 inch dia. spring-wire guide