



REF **PR-35563-TTS** (IPNXXXXXX)

6 Fr. **3** Lumen **55** cm catheter length **.018** inch dia. spring-wire guide

Pressure Injectable Three-Lumen PICC pre-loaded with Arrow® VPS TipTracker™ Stylet



Contents:

- 1: Three Lumen TaperFree® Catheter: 6 Fr. (2.14 mm OD) x 55 cm, Pressure Injectable, Blue FlexTip®, Contamination Guard, Arrow® VPS TipTracker™ Stylet and T-Port Connector
 - 1: GlideThru™ Peel-Away Sheath: 6 Fr. x 2-3/4" (7 cm) Radiopaque over 6 Fr. Dilator
 - 1: Placement Wire Assembly
 - 1: Spring-Wire Guide, Nitinol, Marked: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other) with Arrow Advancer
 - 1: Safety Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
 - 1: Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
 - 1: Syringe: 10 mL Luer-Lock
 - 3: Dust Cap: Non-Vented
 - 1: SecondSite™ Adjustable Hub: Fastener
 - 1: SecondSite™ Adjustable Hub: Catheter Clamp
 - 1: SharpsAway® II Locking Disposal Cup
 - 1: SharpsAway® Disposal Cup
 - 1: Catheter Trimmer
 - 1: Safety Scalpel: #11
 - 1: Patient ID Card
 - 1: Patient Information Booklet
 - 2: Paper Tape Measure
 - 1: Tourniquet
 - 1: Foam Electrodes (3 per pack)
 - 1: Dressing: STATLOCK®¹ Catheter Stabilization Device
 - 1: Equipment Cover: 13 cm x 244 cm (5" x 96")
 - 1: T-Piece Cover
- ¹A registered trademark of C. R. Bard, Inc.

All components are CE 2797 unless otherwise noted.



Not made with natural rubber latex.

Contraindications: The Pressure Injectable PICC is contraindicated wherever there is presence of device related infections or presence of thrombosis in the intended insertion vessel or catheter pathway. Clinical assessment of the patient must be completed to ensure no contraindications exist.



Lumen

	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	Pump Flow Rate†† (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (17 Ga.)	0.68	938	5950	6
Medial (18 Ga.)	0.49	277	2540	not rated
Proximal (18 Ga.)	0.50	284	2500	not rated

* Priming volumes are approximate and are done without accessories.

† Flow rate values are approximate and are determined using deionized water at 100 cm head height.

†† Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.

** Pressure injection flow rates are determined at the injector pressure setting of 300 psi maximum using media of 11.8 centipoise viscosity, with 152 cm pressure tubing.

