









16 cm catheter length

Pressure Injectable Arrowg+ard Blue Plus® Three-Lumen CVC

Contents:

- Arrowg+ard Blue Plus®1 Three-Lumen Catheter: 7 Fr. (2.5 mm OD) x 16 cm, Pressure Injectable
- Spring-Wire Guide, Nitinol, Marked: .032" (0.81 mm) dia. x 23-5/8" (60 cm) (Straight Soft Tip on One End "J" Tip on Other) with Arrow Advancer with ECG Mark Introducer Needle: Echogenic 18 Ga. x 2-1/2" (6.35 cm) XTW

- Introducer Needle: Ecnogeriic 10 9a. A 2-1/2 N Syringe: 5 mL Luer-Slip Tissue Dilator: 8 Fr. (2.7 mm) x 9 cm SecondSite™ Adjustable Hub: Fastener SecondSite™ Adjustable Hub: Catheter Clamp SharpsAway® II Locking Disposal Cup
- Safety Scalpel: #11
- ¹Licensed under US Patent No. 7,329,412.

All components are CE 2797 unless otherwise noted.

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU Not made with natural rubber latex.

Store below 25°C (77°F). Avoid excessive heat above 40°C (104°F).

Fluid path components are non-pyrogenic.

Contraindications: The Arrowg+ard Blue Plus antimicrobial catheter is contraindicated for patients with known hypersensitivity to chlorhexidine, silver sulfadiazine and/or sulfa drugs.







Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (16 Ga.)	0.38	2490	10
Medial (18 Ga.)	0.37	1162	5
Proximal (18 Ga.)	0.39	1328	5



[†] Flow rate values are approximate and are determined using deionized water at 100 cm head height.



EU Authorized Representative and Importer:



Teleflex Medical IDA Business and Technology Park
Dublin Road, Athlone
7797 Co. Westmeath, Ireland

Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA



LBL062484 R01 (2023-11)











^{**} Pressure injection flow rates are determined using media of 11.8 centipoise (cP) viscosity, with 152 cm administration set tubing.