PB-10005-000 Dimensions: Width: 6-3/4" (17,2 cm) Length: 11-5/16" (28,7 cm) T04200100A6 Dimensions: 6 5/8" x 10 1/2"

ARROW

CVC 4 LUMEN AGB+ 5 10 MAX Pressure Injectable

REF EU-45854-HPS (IPNXXXXXX)

8.5 Fr. 4 Lumen 20 cm catheter length .032 inch dia. spring-wire guide

Pressure Injectable Arrowg+ard Blue Plus® Four-Lumen CVC

Contents:

1: Arrowg+ard Blue Plus®[1] Four-Lumen Catheter: 8.5 Fr. (3.0 mm OD) x 20 cm, Pressure Injectable
1: Spring-Wire Guide, Nitinol, Marked: .032" (0.81 mm) dia. x 23-5/8" (60 cm) (Straight Soft Tip on One End - "J" Tip on Other) with Arrow Advancer with ECG Mark
1: Introducer Needle: Echogenic 18 Ga. x 2-1/2" (6.35 cm) XTW
1: Pressure Transduction Probe
1: Arrow® Raulerson Spring-Wire Introduction Syringe: 5 mL
1: Tissue Dilator: 9 Fr. x 10.2 cm
4: Dust Cap: Non-Vented
1: SecondSite™ Adjustable Hub: Fastener
1: SecondSite™ Adjustable Hub: Catheter Clamp
1: SharpsAway® II Locking Disposal Cup
1: Safety Scalpel: #11

[1]Licensed under US Patent No. 7,329,412.

All components are CE 2797 unless otherwise noted.

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU

Not made with natural rubber latex.

Store below 25°C (77°F). Avoid excessive heat above 40°C (104°F).

Fluid path components are non-pyrogenic.

Contraindications: The Arrowg+ard Blue Plus antimicrobial catheter is contraindicated for patients with known hypersensitivity to chlorhexidine, silver sulfadiazine and/or sulfa drugs.

MD STERILE EO LATEX 25°C (77°F)

CAS # 7440-48-4

en be hr cs da nl et fi fr de el hu is it lt no pl pt ro ru sr sk sl es sv tr uk

Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (16 Ga.)	0.40	2283	5
Medial 1 (14 Ga.)	0.50	4316	10
Medial 2 (18 Ga.)	0.36	1079	not rated
Proximal (18 Ga.)	0.39	1162	not rated

* Priming volumes are approximate and are done without accessories.

† Flow rate values are approximate and are determined using deionized water at 100 cm head height.

** Pressure injection flow rates are determined using media of 11.8 centipoise (cP) viscosity, with 152 cm administration set tubing.

EU Authorized Representative and Importer:

EC REP Teleflex Medical
IDA Business and Technology Park
Dublin Road, Athlone
Co. Westmeath, Ireland

CE 2797

All components are CE 2797 unless otherwise noted.

Arrow International LLC
Subsidiary of Teleflex Incorporated
3015 Carrington Mill Blvd.
Morrisville, NC 27560 USA

Product of xxx
Packaged in xxx

LOT Lot Number

YYYY-MM-DD YYYY-MM-DD

(01)XXXXXXXXXXXXXX
(17)YYMMDD
(11)YYMMDD
(10)Lot Number

Teleflex®
www.teleflex.com

LBL062507 R02 (2025-05)

CVC 4 LUMEN AGB+ 5 10 MAX Pressure Injectable 8.5 Fr. 4 Lumen 20 cm catheter length .032 inch dia. spring-wire guide

REF EU-45854-HPS

Pressure Injectable Arrowg+ard Blue Plus® Four-Lumen CVC

ARROW