









Arrowg+ard Blue Plus® Three-Lumen CVC Kit

5: Gauze Pad: 4" x 4" (10 cm x 10 cm)1: Surgical Apparel: Impervious Gown

Surgical Apparel: Bouffant Cap

1: Suture: 3-0 Silk with Curved Needle

¹Licensed under US Patent No. 7,329,412.

3Licensed under US Patent No. RE37,814.

1: Tray: Prep

Surgical Apparel: Mask with Eye Shield

²A trademark of Becton, Dickinson and Company.

Contents:

- 1: Arrowg+ard Blue Plus®1 Three-Lumen Catheter: 7 Fr. (2.5 mm OD) x 16
- 1: Spring-Wire Guide, Marked: .032" (0.81 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End "J" Tip on Other) with Arrow Advancer
- 1: Catheter: 18 Ga. x 2-1/2" (6.35 cm) Radiopaque over 20 Ga. RW Introducer Needle
- 1: Introducer Needle: 18 Ga. x 1-1/2" (3.81 cm) XTW
- 1: Pressure Transduction Probe
- Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW and 5 mL Arrow® Raulerson Spring-Wire Introduction Syringe
- Injection Needle: SafetyGlide™2 25 Ga. x 1" (2.54 cm) and 3 mL Luer-Lock Syringe
- 1: Injection Needle: SafetyGlide™2 22 Ga. x 1-1/2" (3.81 cm) and 5 mL
- Luer-Slip Syringe
- 1: Syringe: 10 mL Luer-Lock
- 1: Tissue Dilator: 8.5 Fr. (2.8 mm) x 10.2 cm
- SecondSite™ Adjustable Hub: Fastener
- 1: SecondSite™ Adjustable Hub: Catheter Clamp
- 1: SharpsAway® II Locking Disposal Cup
- 1: SharpsAway® Disposal Cup
- 1: Maximal Barrier Drape™ with 4" fenestration
- 1: Needle Holder
- 1: Forceps
- 1: Safety Scalpel: #11
- 4: Staple Anchoring Devices‡3
- 3: Prep Sponge Swab
- 2: Gauze Pad: 2" x 2" (5 cm x 5 cm)

‡MR Conditional

Not made with natural rubber latex.

Store below 25°C (77°F). Avoid excessive heat above 40°C (104°F).

Contraindications: The Arrowg+ard Blue Plus antimicrobial catheter is contraindicated for patients with known hypersensitivity to chlorhexidine, silver sulfadiazine and/or sulfa drugs.

Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	
Distal (16 Ga.)	0.38	2490	
Medial (18 Ga.)	0.37	1162	
Proximal (18 Ga.)	0.39	1328	

^{*} Priming volumes are approximate and are done without accessories.





LBL062747 R00 (2022-02)

[†] Flow rate values are approximate and are determined using deionized water at 100 cm head height.