



REF PR-41552-BAS (IPNXXXXXX)

5.5 Fr. 2 Lumen 15 cm catheter length .018 inch dia. spring-wire guide

# Pressure Injectable Arrowg+ard Blue Advance® Two-Lumen Midline

**Contents:**

- 1: Two-Lumen TaperFree® Catheter<sup>†††</sup> with Arrowg+ard Blue Advance® Antimicrobial/Antithrombotic Protection<sup>1</sup>: 5.5 Fr. (1.88 mm OD) x 15 cm Pressure Injectable with Blue FlexTip® Feature and Contamination Guard
- 1: GlideThru™ Peel-Away Sheath: 5.5 Fr. x 2-3/4" (7 cm) Radiopaque over 5.5 Fr. Dilator
- 1: Spring-Wire Guide, Nitinol, Marked: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other)
- 1: Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- 1: Syringe: 10 mL Luer-Lock
- 2: Dust Cap: Non-Vented
- 1: SecondSite™ Adjustable Hub: Fastener
- 1: SecondSite™ Adjustable Hub: Catheter Clamp
- 1: SharpsAway® II Locking Disposal Cup
- 1: SharpsAway® Disposal Cup
- 1: Catheter Trimmer
- 1: Safety Scalpel: #11
- 1: Overbed Sign
- 1: Patient Information Booklet
- 1: Paper Tape Measure
- 1: Dressing: STATLOCK®<sup>2</sup> PICC Plus Catheter Stabilization Device

<sup>1</sup>Licensed under US Patent No. 7,329,412 and 11,219,706.

<sup>2</sup>A registered trademark of C. R. Bard, Inc.

**Rx only**

**Warning:** Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. [www.teleflex.com/IFU](http://www.teleflex.com/IFU)

California Prop. 65

**⚠ WARNING:** Cancer and Reproductive Harm.

[www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov)

**##MR Safe**

**Not made with natural rubber latex.**

Store below 25°C (77°F). Avoid excessive heat above 30°C (86°F).

Fluid path components are non-pyrogenic.

**Contraindications:** The Arrowg+ard Blue Advance Pressure Injectable Midline is contraindicated for patients with known hypersensitivity to chlorhexidine.



Lumen

|                   | Priming Volume* (mL) | Gravity Flow Rate† (mL/hr) | Pump Flow Rate†† (mL/hr) | MAX Pressure Injection Flow Rate** (mL/sec) |
|-------------------|----------------------|----------------------------|--------------------------|---|
| Distal (18 Ga.)   | 0.30                 | 1071                       | 5860                     | 5   |
| Proximal (18 Ga.) | 0.31                 | 898                        | 6660                     | not rated                                   |

\* Priming volumes are approximate and are done without accessories.

† Flow rate values are approximate and are determined using deionized water at 100 cm head height.

†† Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.

\*\* Pressure injection flow rates are determined using media of 11.8 centipoise (cP) viscosity, with 152 cm administration set tubing.



en fr-CA pt-BR es-MX



LOT Lot Number

YYYY-MM-DD

YYYY-MM-DD



(01)XXXXXXXXXXXXXX  
(17)YYMMDD  
(11)YYMMDD  
(10)Lot Number

CAS # 7440-48-4



Arrow International LLC  
Subsidiary of Teleflex Incorporated  
3015 Carrington Mill Blvd.  
Morrisville, NC 27560 USA

Product of xxx  
Packaged in xxx

**Teleflex®**  
[www.teleflex.com](http://www.teleflex.com)