



REF PR-05052

50 cm catheter length

1018 inch dia. spring-wire guide

Two-Lumen PICC

- Two Lumen Catheter: 16 Ga. (1.76 mm OD) x 50 cm, Blue FlexTip® GlideThru™ Peel-Away Sheath: 5 Fr. x 4" (10 cm) Radiopaque over
- 5 Fr. Dilator
- Spring-Wire Guide: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other) Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- Syringe: 5 mL Luer-Slip

- Dust Cap: Non-Vented
 SecondSite™ Adjustable Hub: Fastener
 SecondSite™ Adjustable Hub: Catheter Clamp
- Chart Sticker
- Patient Information Booklet
- Patient ID Card
- Paper Tape Measure
- Dressing: STATLOCK®1 PICC Plus Catheter Stabilization Device

¹A registered trademark of C. R. Bard, Inc.

All components are CE 2797 unless otherwise noted.

Rx only

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU

Not made with natural rubber latex.

Fluid path components are non-pyrogenic.

Contraindications: The PICC is contraindicated wherever there is presence of device related infections or presence of thrombosis in the intended insertion vessel or catheter pathway. Clinical assessment of the patient must be completed to ensure no contraindications exist.






















Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	Pump Flow Rate†† (mL/hr)	
Distal (18 Ga.)	0.41	436	3182	
Proximal (20 Ga.)	0.39	172	1874	

Priming volumes are approximate and are done without accessories.



EU Authorized Representative and Importer:



Teleflex Medical IDA Business and Technology Park
Dublin Road, Athlone
7797 Co. Westmeath, Ireland

Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA



LBL063361 R01 (2023-09)




















[†] Flow rate values are approximate and are determined using deionized water at 100 cm head height.

^{††} Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.