



REF SI-11142

(IPNXXXXXX)



10 cm device length .035 inch dia. spring-wire guide

MAC™ Two-Lumen Central Venous Access Set with Integral Hemostasis Valve for use with 7 - 8 Fr. Catheters

- Two-Lumen Central Venous Access Device: 4" (10 cm) Radiopaque Polyurethane with 9
- Fr. Distal Lumen, Integral Hemostasis Valve, Extension Line Clamps
 Spring-Wire Guide, Marked: .035" (0.89 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on
 One End "J" Tip on Other) with Arrow Advancer
 Introducer Needle: 18 Ga. x 2-1/2" (6.35 cm) XTW
 Pressure Transduction Probe

- Arrow® Raulerson Spring-Wire Introduction Syringe: 5 mL
- Tissue Dilator: 9 Fr. (3.0 mm) x 20.7 cm
- Obturator: 8 Fr.
 Cath-Gard® Catheter Contamination Shield: 80 cm with Tuohy-Borst Adapter, Sterile Tape

- Cath-Gard® Catheter Contamination
 Dust Cap: Vented
 Dust Cap: Non-Vented
 Stopcock: 4-way High-Flow
 Gauze Pad: 4" x 4" (10 cm x 10 cm)

All components are CE 2797 unless otherwise noted.

Rx	on	l১
----	----	----

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU

California Prop. 65

M WARNING: Cancer and Reproductive Harm.

www.P65Warnings.ca.gov
Not made with natural rubber latex.

Fluid path components are non-pyrogenic.

Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)
Distal (9 Fr.) no catheter	1.65	31440
Distal (9 Fr.) with 8 Fr. catheter	0.9	9040
Proximal (12 Ga.) no catheter	0.6	8970


^{*} Priming volumes are approximate and are done without accessories.















(01)XXXXXXXXXXXXXXX (17)YYMMDD (11)YYMMDD (10)LotNumber





All components are CE 2797 unless

Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA

Product of xxx Packaged in xxx



LBL064085 R01 (2024-05)



MAC™ Two-Lumen Central Venous Access Set with Integral Hemostasis Valve for use with 7 - 8 Fr. Catheters



ARR(



 $10^{\,\text{cm}}_{\,\text{device}}$

.035 inch dia. spring-wire guide



[†] Flow rate values are approximate and are determined using deionized water at 100 cm head height.