



(IPNXXXXXX)





## **Pressure Injectable Two-Lumen PICC**

## Contents:

- Two Lumen TaperFree® Catheter: 5 Fr. (1.81 mm OD) x 50 cm, Pressure Injectable, T-Port Connector, Blue FlexTip®, Contamination Guard and
- GlideThru™ Peel-Away Sheath: 5 Fr. x 2-3/4" (7 cm) Radiopaque over 5 Fr.
- Spring-Wire Guide, Nitinol, Marked: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other) with Arrow Advancer
- Injection Needle: SafetyGlide™1 25 Ga. x 5/8" (1.60 cm) RW
- Safety Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- Introducer Needle: Echogenic 21 Ga, x 2-3/4" (7 cm) TW

- SecondSite™ Adjustable Hub: Catheter Clamp

- Maximal Barrier Drape™ with two 13 cm (5") x 15 cm (6") fenestrations

Not made with natural rubber latex.

- <sup>1</sup>A trademark of Becton, Dickinson and Company.
- <sup>2</sup>A registered trademark of 3M Company.
- All components are CE 2797 unless otherwise noted.

Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	Pump Flow Rate†† (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (18 Ga.)	0.48	488	3860	5
Proximal (18 Ga.)	0.5	488	3870	5

<sup>\*</sup> Priming volumes are approximate and are done without accessories.



contraindications exist.



Contraindications: The Pressure Injectable PICC is contraindicated wherever there is presence of device related infections or presence of thrombosis in the intended insertion vessel or catheter pathway. Clinical assessment of the patient must be completed to ensure no

LBL064591 R03 (2024-05)

<sup>†</sup> Flow rate values are approximate and are determined using deionized water at 100 cm head

<sup>††</sup> Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.

<sup>\*\*</sup> Pressure injection flow rates are determined at the injector pressure setting of 300 psi maximum using media of 11.8 centipoise viscosity, with 152 cm pressure tubing.