







(IPNXXXXXX)

55 cm catheter length



Pressure Injectable Arrowg+ard Blue Advance® Three-Lumen PICC pre-loaded with Arrow® VPS TipTracker™ Stylet



Contents:

- 1: Three Lumen TaperFree® Catheter with Arrowg+ard Blue Advance® Antimicrobial/Antithrombogenic Protection¹: 6 Fr. (2.11 mm OD) x 55 cm. Pressure Injectable, Blue FlexTip®, Arrow® TipTracker™ Stylet and T-Port
- GlideThru™ Peel-Away Sheath: 6 Fr. x 2-3/4" (7 cm) Radiopaque over 6 Fr.
- Spring-Wire Guide, Nitinol, Marked: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other) with Arrow Advancer
- Iniection Needle: Eclipse™2 25 Ga. x 1" (2.54 cm) RW
- Safety Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
- Syringe: 10 mL Luer-Lock
- Syringe: 3 mL Luer-Lock
- Dust Cap: Non-Vented
- SecondSite™ Adjustable Hub: Fastener
- SecondSite™ Adjustable Hub: Catheter Clamp
- SharpsAway® II Locking Disposal Cup
- SharpsAway® Disposal Cup
- Catheter Trimmer
- Towel: 24" x 36" (61 cm x 91 cm)

Not made with natural rubber latex.

Maximal Barrier Drape™ with two 13 cm (5") x 15 cm (6") fenestrations

Store below 25°C (77°F). Avoid excessive heat above 30°C (86°F).

for patients with known hypersensitivity to chlorhexidine

- Safety Scalpel: #11
- Patient ID Card
- Patient Information Booklet
- Paper Tape Measure
- 1: Tourniquet

- 1: Foam Electrodes (3 per pack)
- 10: Gauze Pad: 2" x 2" (5 cm x 5 cm)
- Gauze Pad: 4" x 4" (10 cm x 10 cm)
- Dressing: Tegaderm®3 15.5 cm x 10 cm
- Surgical Apparel: Impervious Gown
- Dressing: STATLOCK®4 Catheter Stabilization Device
- Surgical Apparel: Mask with Eye Shield
- Surgical Apparel: Bouffant Cap
- Surgical Apparel: Mask
- Equipment Cover: 13 cm x 244 cm (5" x 96")
- Tape: Steri-Strip®3
- HemoHopper® Fluid Receptacle
- 1: T-Piece Cover
- ¹Licensed under US Patent No. 7,329,412.
- ²A trademark of Becton, Dickinson and Company
- ³A registered trademark of 3M Company.
- ⁴A registered trademark of C. R. Bard, Inc.
- All components are CE 2797 unless otherwise noted.



Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	Pump Flow Rate†† (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (18 Ga.)	0.61	880	5360	6
Medial (19 Ga.)	0.45	244	2090	not rated
Proximal (19 Ga.)	0.47	257	2160	not rated

^{*} Priming volumes are approximate and are done without accessories.







• in the presence of device related infection in the intended insertion vessel or catheter pathway

• in the presence of thrombosis in the intended insertion vessel or catheter pathway

Contraindications: The Pressure Injectable Arrowg+ard Blue Advance antimicrobial/antithrombogenic catheter is contraindicated:

LBL064663 R02 (2024-01)

[†] Flow rate values are approximate and are determined using deionized water at 100 cm head height.

^{††} Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.

^{**} Pressure injection flow rates are determined at the injector pressure setting of 300 psi maximum using media of 11.8 centipoise viscosity, with 152 cm pressure tubing.