



REF EU-24052-HPMSB

40 cm catheter length 018 inch dia. spring-wire guide

Pressure Injectable Two-Lumen PICC

Contents:

- Two Lumen Catheter: 5 Fr. (1.81 mm OD) x 40 cm, Pressure Injectable, T-Port
- Connector, Blue FlexTip®, Contamination Guard and Placement Wire GlideThru™ Peel-Away Sheath: 5 Fr. x 2-3/4" (7 cm) Radiopaque over 5 Fr.
- Dilator
 Spring-Wire Guide, Nitinol, Marked: .018" (0.46 mm) dia. x 17-3/4" (45 cm)
 (Straight Soft Tip on One End Straight Stiff Tip on Other) with Arrow Advancer Injection Needle: Eclipse™ 129 Ga. x 1-5/8" (4 cm)
 Injection Needle: Eclipse™ 25 Ga. x 1" (2.54 cm)
 Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW
 Filter Needle: 18 Ga. TW x 1-1/2" (3.81 cm) with Blunt Fill Tip

- Filter Needle: 18 Ga. 1W x 1-1/2" (3.81 cm) witr Syringe: 10 mL Luer-Lock Syringe: 3 mL Luer-Lock SecondSite™ Adjustable Hub: Fastener SecondSite™ Adjustable Hub: Catheter Clamp SharpsAway® II Locking Disposal Cup SharpsAway® Disposal Cup Catheter Trimmer

- Catheter I finmer
 Towel: 24" x 36" (61 cm x 91 cm)
 Drape: 60" x 76" (152 cm x 193 cm)
 Drape: 36" x 41" (91 cm x 104 cm) with 3" x 5" (8 cm x 13 cm) fenestration
 Towel
- Safety Scalpel: #11 Patient ID Card
- Sterile Procedure Sign Patient Information Booklet Chart Sticker
- PICC Line Insertion Checklist Paper Tape Measure

- Gauze Pad: 4" x 4" (10 cm x 10 cm)
 Gauze Pad: 2" x 2" (5 cm x 5 cm)
 Dressing: Tegaderm[®] 2 I.V. Advanced 3-1/4" x 4-1/2" (8.5 cm x 11.5 cm)
 Dressing: GRIP-LOK[®] 3 Catheter Fixation Device
 Surgical Apparel: Cap

- Surgical Apparel: Impervious Gown Dressing: Steri-Strip®2 1/2" x 4" (1.2 cm x 10 cm) Surgical Apparel: Mask
- Surgical Apparel: Mask with Shield Transducer Cover: 4-12/16" x 95" (12 cm x 244 cm) Valve: MicroCLAVE™4 Neutral Displacement Connector
- HemoHopper® Fluid Receptacle
- ¹A trademark of Becton, Dickinson and Company.

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU

Not made with natural rubber latex. Fluid path components are non-pyrogenic

Contraindications: The Pressure Injectable PICC is contraindicated wherever there is presence of device related infections or presence of thrombosis in the intended insertion vessel or catheter pathway. Clinical assessment of the patient must be completed to ensure no

Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	Pump Flow Rate†† (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (18 Ga.)	0.36	416	3500	4 4
Proximal (18 Ga.)	0.38	475	4090	

* Priming volumes are approximate and are done without accessories. † Flow rate values are approximate and are determined using deionized water at 100 cm head

²A registered trademark of 3M Company.

All components are CE 2797 unless otherwise noted

³A registered trademark of TIDI. ⁴A trademark of ICU Medical, Inc.

†† Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.

** Pressure injection flow rates are determined at the injector pressure setting of 300 psi maximum using media of 11.8 centipoise viscosity, with 152 cm pressure tubing.



STERILE EO





Arrow International LLC Subsidiary of Teleflex Incorporated 3015 Carrington Mill Blvd. Morrisville, NC 27560 USA



LBL069856 R02 (2023-12)



MD [

LOT











40 cm catheter length .018 inch dia. spring-wire quide

