



REF EU-24063-HPMSB (IPNXXXXXX)

6 Fr. 3 Lumen 40 cm catheter length .018 inch dia. spring-wire guide



Pressure Injectable Three-Lumen PICC

Contents:

- 1: Three Lumen Catheter: 6 Fr. (2.14 mm OD) x 40 cm, Pressure Injectable, T-Port Connector, Blue FlexTip®, Contamination Guard and Placement Wire

1: GlideThru™ Peel-Away Sheath: 6 Fr. x 2-3/4" (7 cm) Radiopaque over 6 Fr. Dilator

1: Spring-Wire Guide, Nitinol, Marked: .018" (0.46 mm) dia. x 17-3/4" (45 cm) (Straight Soft Tip on One End - Straight Stiff Tip on Other) with Arrow Advancer

1: Injection Needle: Eclipse™¹ 23 Ga. x 1" (2.54 cm)

1: Injection Needle: Eclipse™¹ 25 Ga. x 1" (2.54 cm)

1: Introducer Needle: Echogenic 21 Ga. x 2-3/4" (7 cm) TW

1: Filter Needle: 18 Ga. TW x 1-1/2" (3.81 cm) with Blunt Fill Tip

2: Syringe: 10 mL Luer-Lock

1: Syringe: 3 mL Luer-Lock

1: SecondSite™ Adjustable Hub: Fastener

1: SecondSite™ Adjustable Hub: Catheter Clamp

1: SharpsAway® II Locking Disposal Cup

1: SharpsAway® Disposal Cup

1: Catheter Trimmer

1: Towel: 24" x 36" (61 cm x 91 cm)

1: Drape: 60" x 76" (152 cm x 193 cm)

1: Drape: 36" x 41" (91 cm x 104 cm) with 3" x 5" (8 cm x 13 cm) fenestration

1: Towel

1: Safety Scalpel: #11

1: Patient ID Card

1: Sterile Procedure Sign

1: Patient Information Booklet

1: Chart Sticker
- 1: PICC Line Insertion Checklist

1: Paper Tape Measure

1: Tourniquet

5: Gauze Pad: 2" x 2" (5 cm x 5 cm)

10: Gauze Pad: 4" x 4" (10 cm x 10 cm)

1: Dressing: Tegaderm®² I.V. Advanced 3-1/4" x 4-1/2" (8.5 cm x 11.5 cm)

1: Dressing: GRIP-LOK®³ Catheter Fixation Device

1: Surgical Apparel: Cap

1: Surgical Apparel: Impervious Gown

1: Dressing: Steri-Strip®² 1/2" x 4" (1.2 cm x 10 cm)

1: Surgical Apparel: Mask

1: Surgical Apparel: Mask with Shield

1: Transducer Cover: 4-12/16" x 95" (12 cm x 244 cm)

3: Valve: MicroCLAVE™⁴ Neutral Displacement Connector

1: HemoHopper® Fluid Receptacle

¹A trademark of Becton, Dickinson and Company.

²A registered trademark of 3M Company.

³A registered trademark of TIDI.

⁴A trademark of ICU Medical, Inc.

All components are CE 2797 unless otherwise noted.

Warning: Read all package insert warnings, precautions, and instructions prior to use. Failure to do so may result in severe patient injury or death. www.teleflex.com/IFU

Not made with natural rubber latex.

Fluid path components are non-pyrogenic.

Contraindications: The Pressure Injectable PICC is contraindicated wherever there is presence of device related infections or presence of thrombosis in the intended insertion vessel or catheter pathway. Clinical assessment of the patient must be completed to ensure no contraindications exist.

Lumen	Priming Volume* (mL)	Gravity Flow Rate† (mL/hr)	Pump Flow Rate†† (mL/hr)	MAX Pressure Injection Flow Rate** (mL/sec)
Distal (17 Ga.)	0.55	1370	6800	6
Medial (19 Ga.)	0.44	317	2820	not rated
Proximal (19 Ga.)	0.42	317	2920	not rated

* Priming volumes are approximate and are done without accessories.
† Flow rate values are approximate and are determined using deionized water at 100 cm head height.
†† Pump flow rates are determined at maximum pump pressure of 10 psig and represent approximate flow capabilities.
** Pressure injection flow rates are determined at the injector pressure setting of 300 psi maximum using media of 11.8 centipoise viscosity, with 152 cm pressure tubing.



EU Authorized Representative and Importer:



Teleflex Medical
IDA Business and
Technology Park
Dublin Road, Athlone
Co. Westmeath, Ireland

All components are CE 2797 unless otherwise noted.



Arrow International LLC
Subsidiary of Teleflex Incorporated
3015 Carrington Mill Blvd.
Morrisville, NC 27560 USA

Product of xxx
Packaged in xxx

Teleflex®
www.teleflex.com
LBL069857 R04 (2025-01)



CAS # 7440-48-4

LOT Lot Number



YYYY-MM-DD



YYYY-MM-DD



(01)XXXXXXXXXXXXXX
(17)YYMMDD
(11)YYMMDD
(10)Lot Number



Pressure Injectable Three-Lumen PICC

REF EU-24063-HPMSB

6 Fr. 3 Lumen 40 cm catheter length .018 inch dia. spring-wire guide

